

Overview

The HP ProLiant ML350p Gen8 Server series is the latest generation of the best-selling ProLiant ML servers delivering best-inclass performance, availability and maximum expandability for enterprise data centers, remote branch offices and growing businesses. Incorporating key HP technologies from the HP ProActive Insight architecture, the ML350p Gen8 provides innovations in memory, server management, firmware management and server storage. It combines these innovations with the latest Intel® Xeon® processors for a system with unsurpassed flexibility and performance.





Front View:

- 1. Half height SATA DVD ROM or DVD RW optical drive
- 2. Two (2) removable media bays
- 3. Systems Insight Display (rack and CTO models only)
- 4. Four (4) system fans
- 5. Twenty-four (24) DIMM slots: DDR3 Load Reduced (LRDIMM), Registered (RDIMM) or Unbuffered (UDIMM)
- 6. Nine (9) PCIe expansion slots (8 PCIe 3.0 and 1 PCIe 2.0) 6.
- 7. Two (2) processor heatsinks
- 8. Quick removal access panel
- 9. Power On / Standby button and system power LED button 9.
- 10. NIC Activity LED
- 11. Health LED
- 12. UID LED button
- 13. Optional drive cage
- 14. Standard drive cage (6 LFF or 8 SFF)
- 15. Four (4) USB connectors

Rear View:

- 1. Power supply 1(CTO)
- 2. Power supply 2(CTO)
- 3. Power supply 3 (Default)
- 4. Power supply 4 (Default)
- 5. Four (4) PCIe slots (for processor 1)
 - UID LED button
- 7. Serial connector
- 8. iLO connector
- 9. NIC connector 4
- 10. NIC connector 3
- 11. NIC connector 2
- 12. NIC connector 1
- 13. Four (4) USB connectors
- 14. Video connector
- 15. Five (5) PCle slots (for processor 2)

What's New

 Support for 12G SAS High Endurance Hot Plug SFF (2.5-inch) Enterprise Performance and Enterprise Mainstream Solid State Drives



Standard Features

NOTE: For the Standard Features shipped in the "Factory Integrated Models", please see the "Configuration Information - Factory Integrated Models" section.

Processor

One of the following depending on Model

E5-2600 v2 series Processors

Entry Processors

NOTE: All support up to 1333MHz DDR3 memory speeds.

Intel® Xeon® E5-2609 v2 (2.5GHz/4-core/10MB/6.4GT-s QPI/80W)

Intel® Xeon® E5-2603 v2 (1.8GHz/4-core/10MB/6.4GT-s QPI/80W)

Base Processors

NOTE: All support up to 1600MHz DDR3 memory speeds.

Intel® Xeon® E5-2640 v2 (2.0GHz/8-core/20MB/7.2GT-s QPI/95W, DDR3-1600, HT, Turbo2-3/3/3/3/4/5)

Intel® Xeon® E5-2630 v2 (2.6GHz/6-core/15MB/7.2GT-s QPI/80W, DDR3-1600, HT, Turbo2-3/3/3/4/5)

Intel® Xeon® E5-2620 v2 (2.1GHz/6-core/15MB/7.2GT-s QPI/80W, DDR3-1600, HT, Turbo2-3/3/3/4/5)

Intel® Xeon® E5-2630L v2 (2.4GHz/6-core/15MB/7.2GT-s QPI/60W, DDR3-1600, HT, Turbo2-2/2/2/3/4)

Performance Processors

NOTE: All support up to 1866MHz DDR3 memory speeds.

Intel® Xeon® E5-2697 v2 (2.7GHz/12-core/30MB/8.0GT-s QPI/130W, DDR3-1866, HT, Turbo2-3/3/3/3/3/4/5/6/7/8)

Intel® Xeon® E5-2690 v2 (3.0GHz/10-core/25MB/8.0GT-s QPI/130W, DDR3-1866, HT, Turbo2-3/3/3/3/3/3/4/5/6)

Intel® Xeon® E5-2680 v2 (2.8GHz/10-core/25MB/8.0GT-s QPI/115W, DDR3-1866, HT, Turbo2-3/3/3/3/4/5/6/7/8)

Intel® Xeon® E5-2670 v2 (2.5GHz/10-core/25MB/8.0GT-s QPI/115W, DDR3-1866, HT, Turbo2-4/4/4/4/4/5/6/7/8)

Intel® Xeon® E5-2667 v2 (3.3GHz/8-core/25MB/8.0GT-s QPI/130W, DDR3-1866, HT, Turbo2-3/3/3/4/5/6/7)

Intel® Xeon® E5-2650 v2 (2.6GHz/8-core/20MB/8.0GT-s QPI/95W, DDR3-1866, HT, Turbo2-4/4/4/5/6/7/8)

Intel® Xeon® E5-2643 v2 (3.5GHz/6-core/25MB/8.0GT-s QPI/130W, DDR3-1866, HT, Turbo2-1/1/1/2/3)

Intel® Xeon® E5-2637 v2 (3.5GHz/4-core/15MB/8.0GT-s QPI/130W, DDR3-1866, HT, Turbo2-1/1/2/3)

E5-2600 series Processors

Entry Processors

NOTE: All support up to 1066MHz DDR3 memory speeds.

Intel® Xeon® E5-2609 (2.4GHz/4-core/10MB/6.4GT-s QPI/80W)

Intel® Xeon® E5-2603 (1.8GHz/4-core/10MB/6.4GT-s QPI/80W)

Base Processors

NOTE: All support up to 1333MHz DDR3 memory speeds.

Intel® Xeon® E5-2640 (2.5GHz/6-core/15MB/7.2GT-s QPI/95W, DDR3-1333, HT, Turbo2-3/3/4/4/5/5)

Intel® Xeon® E5-2630 (2.3GHz/6-core/15MB/7.2GT-s QPI/95W, DDR3-1333, HT, Turbo2-3/3/4/4/5/5)



Standard Features

Intel® Xeon® E5-2620 (2.0GHz/6-core/15MB/7.2GT-s QPI/95W, DDR3-1333, HT, Turbo2-3/3/4/4/5/5)

Intel® Xeon® E5-2630L (2.0GHz/6-core/15MB/8.0GT-s QPI/60W, DDR3-1333, HT, Turbo2-3/3/4/4/5/5)

Performance Processors

NOTE: All support up to 1600MHz DDR3 memory speeds.

Intel® Xeon® E5-2690 (2.9GHz/8-core/20MB/8.0GT-s QPI/135W, DDR3-1600, HT, Turbo2-4/4/5/5/7/79)

Intel® Xeon® E5-2680 (2.7GHz/8-core/20MB/8.0GT-s QPI/130W, DDR3-1600, HT, Turbo2-4/4/5/5/7/8/8)

Intel® Xeon® E5-2670 (2.6GHz/8-core/20MB/8.0GT-s QPI/115W, DDR3-1600, HT, Turbo2-4/4/5/5/6/6/7/7)

Intel® Xeon® E5-2667 (2.9GHz/6-core/15MB/8.0GT-s QPI/130W, DDR3-1600, HT, Turbo2-3/3/3/4/5/6)

Intel® Xeon® E5-2665 (2.4GHz/8-core/20MB/8.0GT-s QPI/115W, DDR3-1600, HT, Turbo2-4/4/5/5/6/6/7/7)

Intel® Xeon® E5-2660 (2.2GHz/8-core/20MB/8.0GT-s QPI/95W, DDR3-1600, HT, Turbo2-5/5/6/6/7/7/8/8)

Intel® Xeon® E5-2650 (2.0GHz/8-core/20MB/8.0GT-s QPI/95W, DDR3-1600, HT, Turbo2-4/4/5/5/5/7/8/8)

Intel® Xeon® E5-2650L (1.8GHz/8-core/20MB/8.0GT-s QPI/70W, DDR3-1600, HT, Turbo2-2/2/3/3/4/4/5/5)

Intel® Xeon® E5-2643 (3.3GHz/4-core/10MB/8.0GT-s QPI/130W, DDR3-1600, HT, Turbo2- 1/1/2/2)

Intel® Xeon® E5-2637 (3.0GHz/2-core/5MB/8.0GT-s QPI/80W, DDR3-1600, HT, Turbo2- 5/5)

NOTE: HT indicates that the processor model supports Intel® Hyper-Threading Technology.

NOTE: Turbo indicates the maximum potential frequency increment when using Intel® Turbo Boost Technology, with 8, 7, 6, 5, 4, 3, 2 or 1 core(s) active.

NOTE: DDR3 speed is the maximum memory speed of the processor. Actual memory speed may depend on the quantity and type of DIMMs installed.

NOTE: Up to 2 processors supported. Mixing different processor models is not supported. **NOTE:** For the Intel® C600 Chipset E5-2600 Series, the letter preceding the model number indicates the Product Line (E3, E5, E7); 2600x, 2 = number of CPUs in a Node, 6 is socket/segment designation, 00 = Processor SKU, and x = L for low power SKUs.

Cache Memory

One of the following depending on Model

30MB (1 x 30MB) Level 3

NOTE: For Twelve-core processors.

25MB (1 x 25MB) Level 3

NOTE: For Ten-core processors.

20MB (1 x 20MB) Level 3

NOTE: For Eight-core processors.

15MB (1 x 15MB) Level 3

NOTE: For Six-core processors.

10MB (1 x 10MB) Level 3

NOTE: For Quad-core processors.

5MB (1 x 5MB) Level 3

NOTE: For Dual-Core processors.



Standard Features

Chipset Intel® C600 Chipset

Intel® E5-2600 Processor Family Intel® E5-2600v2 Processor Family

NOTE: For more information regarding Intel® chipsets, please see the following URL:

http://www.intel.com/products/server/chipsets/.

Upgradeability Upgradeable to two processors

NOTE: Total 4, 8, 12, 16, 20 or 24 cores

NOTE: Processor upgrade available from Intel® Xeon® Processors E5-2600 to E5-2600 v2. Please contact HP Technology Sales (http://www.hp.com/support), your local HP Re-seller, or reference the following Customer Advisory: ProLiant Servers-Instructions for Upgrading an HP ProLiant Gen8 Server from an Intel Xeon Processor E5-2600 to an Intel Xeon Processor E5-2600 v2, regarding critical details before upgrading. An explanation of requirements and limitations are provided. **NOTE:** Customers who use ML350p Gen8 sandy bridge processors need to purchase Heatsink

lever upgrade kit 749245-B21 when plan to upgrade to Ivy bridge processor

Up to 24 DIMM slots available for higher memory capacity Up to 24 SFF Hard Drive Bays; Or 18 LFF Hard Drive Bays

8 PCIe 3.0 and 1 PCIe 2.0 I/O slots for additional communications and storage expansion

Redundant Power Supply and Redundant Fans

Optical Drive Bay (up to 3)

On System ManagementHP iLO (Firmware: HP iLO4)

Chipset NOTE: For more information, visit: http://www.hp.com/go/ilo

Memory Protection Advanced ECC

Online Spare Lock-step mode

Memory Type HP SmartMemory

DDR3 Load Reduced (LRDIMM), Registered (RDIMM) or Unbuffered

(UDIMM)

DIMM Slots Available 24

Maximum Capacity 768GB (24 x 32GB LRDIMM @1866MHz)

(LRIDMM)

Maximum Capacity 384GB (24x 16GB RDIMM @1866MHz)

(RDIMM)

Maximum Capacity 128GB (16 x 8GB UDIMM @1866MHz)

(UDIMM)

NOTE: HP memory from previous generation servers are not qualified or warranted with this HP ProLiant Server. HP SmartMemory is required to realize the memory performance improvements and enhanced functionality listed in this document for Gen8. For additional information, please see the HP SmartMemory QuickSpecs at:

http://h18000.www1.hp.com/products/quickspecs/14225 div/14225 div.html

NOTE: LRDIMM, RDIMM and UDIMMs are all distinct memory technologies and cannot be mixed within a server. The majority of ProLiant Gen8 servers support RDIMM, UDIMM and LRDIMM.



Standard Features

NOTE: If only one processor is installed, only 12 DIMM slots are available. When populating with two processors 24 DIMM slots are available. For maximum speed on some memory options on 16 DIMM slots may be populated.

NOTE: Depending on the memory configuration and processor model, the memory speed may run at 1866MHz, 1600MHz, 1333MHz, or 1066MHz. Please see Memory Population Table or the Online Memory Configuration Tool at: www.hp.com/go/ddr3memory-configurator.

Network Controller

HP 1Gb Ethernet 4-port 331i Adapter

Expansion Slots

Expansion Slot #	Technology	Bus Width	Connector Width	Bus Number	Form Factor	Notes
9	PCle 3.0	x4	x8	32	Full Length/Full Height	For processor 2
8	PCIe 3.0	x16	x16	32	Full Length/Full Height	For processor 2
7	PCIe 3.0	х4	x 8	32	Full Length/Full Height	For processor 2
6	PCIe 3.0	x16	x16	32	Full Length/Full Height	For processor 2
5	PCIe 2.0	x4	x8	0	Half Length/Full Height	For processor 2
4	PCIe 3.0	x4	x8	0	Full Length/Full Height	For processor 1
3	PCIe 3.0	x16	x16	0	Full Length/Full Height	For processor 1
2	PCIe 3.0	x4	x8	0	Full Length/Full Height	For processor 1
1	PCIe 3.0	x8	x16	0	Full Length/Full Height	For processor 1

NOTE: Bus number - Default bus assignment (in decimal). Inserting cards with PCI bridges may alter the actual bus assignment number.

NOTE: Nine total expansion slots. Three PCle 3.0 x16 (x16 speed); One PCle 3.0 x16 (x8 speed); Four PCle 3.0 x8 (x4 speed); One PCle 2.0 x8 (x4 speed).



Standard Features

HP Server ROM

HP ROM (Read Only Memory) is now digitally signed using HP's Corporate Signing Service. This signature is verified before the flash process starts, reducing accidental programming and preventing malicious efforts to corrupt system ROM.

HP ROM provides for essential initialization and validation of hardware components before control is passed to the customer-installed operating system. The ROM also provides the capability of booting from various fixed media (HDD, CD-ROM) and removable media (USB), to continue operation to the operating system.

HP ROM performs very early configuration of the video controller, to allow monitoring of initialization progress via an attached monitor. If configuration or hardware errors are discovered during this early phase of hardware initialization, suitable messages are now displayed on the connected monitor. Additionally, these configuration or hardware errors are logged to the Integrated Management Log (IML) to assist in diagnosis.

HP's ProLiant ROM is used to configure the following:

- Processor and chipset status registers
- System memory, memory map, and memory initialization
- System hardware configuration (Integrated PCI devices and optional PCIe cards).
- Customer-specific BIOS configuration (using the HP ROM-Based Setup Utility (RBSU).

NOTE: For further information, please refer to HP's RBSU (ROM based setup utility) user guide: www.hp.com/support/rbsu.

Storage Controller
One of the following
depending on model

Entry Models HP Smart Array P420i/Zero Memory Controller

Base Models HP Smart Array P420i/512M FBWC Controller (RAID

0/1/1+0/5/5+0/6/6+0)

NOTE: The SA-P420i/512M FBWC is standard on tower model and SA-

P420i/1G FBWC is standard on rack model.

HP Smart Array P420i/1G FBWC Controller (RAID 0/1/1+0/5/5+0/6/6+0)

Performance Models

HP Smart Array P420i/2G FBWC Controller (RAID 0/1/1+0/5/5+0/6/6+0)

Internal Storage Devices

Optical Drives

One of the following depending on model

HP Half-Height SATA DVD-ROM Optical Drive

NOTE: DVD ROM is standard in entry and base tower models.

HP Half Height SATA DVD-RW Optical Drive

NOTE: DVD-RW is standard in performance tower and all rack models.

None ship standard

Hard Drives Hard Drive Bays One of the following

One of the following depending on model

(6) Hot plug LFF SAS/SATA HDD bays; upgradable to (18)

(8) Hot plug SFF SAS/SATA HDD bays; upgradable to (24)

NOTE: All Pre-configured Models come populated with some hard drive blanks installed. Should the customer need additional hard drive blanks, they can order more using either P/N 666987-B21: HP SFF Gen8 Hard Drive Blank Kit or P/N 666986-B21: HP LFF Gen8 Hard Drive Blank Kit. These part numbers for single HDD blanks below are also provided should the customer require replacement HDD blanks for their server.



Standard Features

Maxir	num	In	terna	al
Stora	ge			
_				

One of the following depending on model

72TB	18 x 4TB
72TB	18 x 4TB
28.8TB	24 x 1.2TB
24TB	24 x 1TB
9.6TB	24 x 400GB
19.2TB	24 x 800GB
7.2TB	18 x 400GB
	72TB 28.8TB 24TB 9.6TB 19.2TB

Interfaces

Serial 1

Video 1 (rear)

Network RJ-45 (Ethernet) 5 (1 dedicated for HP Integrated Lights-Out) 1 Gb Dedicated

1 (internal)

HP iLO Remote

Management Network

Port

SD slot

NOTE: The SD slot is not a hot-pluggable device. Customers should not

attempt to plug an SD card into the SD slot while the server is powered.

USB 10 (4 front, 4 rear, 2 internal)

Industry Standard Compliance

ACPI 2.0b Compliant PCIe 3.0 Compliant

PXE Support WOL Support Novell Certified

IPMI 2.0, SMASH CLP, DCMI 1.0 compliant

Microsoft® Logo certifications

USB 2.0 Support **SMBIOS 2.7.1**

Server Power Cords

ProLiant ML servers in a rack-mount configuration no longer ship standard with NEMA power cords that allow connection to 110V US wall outlets in a home or office. These servers are primarily connected to PDU's in data center racks so they now ship standard with only a PDU power cord (416151-B21). If a user wishes to power a ProLiant ML rack-mount server using a 110V receptacle (NEMA-15), the NEMA power cord must be ordered separately. The 12' cord (AF556A) or 6' cord (187335-001) can be purchased online at HP.COM. In a tower configuration, the servers ship standard with a 6' country specific NEMA power cord. If customers require a local power cord, they can check the power cord matrix for the appropriate country specific sku. Please see the following power cord matrix: http://www.hp.com/go/powercordmatrix.



Standard Features

Power Specifications

To review typical system power ratings use the HP Power Advisor which is available via the online tool located at URL: www.hp.com/go/proliant-energy-efficient or www.hp.com/go/hppoweradvisor.

NOTE: Power Specification and Technical Content for supported power supplies can be found at: http://h18000.www1.hp.com/products/quickspecs/14209 div/14209 div/html

Common Slot Power Supplies

NOTE: Mixing of power supplies in the same server is not supported. All power supplies inside a server must be exactly the same model. Mixing Gold, Platinum, and Platinum Plus certified power supplies is not supported.

HP's Common Slot (CS) power supplies allow for commonality of power supplies across a wide range of ProLiant and Integrity servers, as well as HP Storage solutions, and are designed to provide the highest power supply efficiency without degrading system performance. HP CS power supplies are tested by the Electric Power Research Institute (EPRI) and certified through the ECOS 80 Plus power supply program. HP CS power supply options provide efficiency ratings of up to 94% (80 Plus Platinum) and are available in three power output options – 460W, 750W, and 1200W - allowing the customer to "right-size" a power supply for their specific server configuration. All HP Common Slot power sources are UL, CE Mark Compliant, hot-plug and support redundant configurations.

NOTE: Mixing of power supplies in the same server is not supported. All power supplies must be of the same output and efficiency rating. If non-matched power supplies are inserted you will get errors and operation will fail.

HP CS Platinum power supplies are required when enabling HP's Intelligent Power Discovery (IPD) solution. IPD is the first technology to create an automated, energy-aware network between IT systems and facilities. This allows your company to reclaim millions of dollars in wasted power capacity and downtime costs across data centers. For more information on HP's IPD solution, go to www.hp.com/go/ipd.

It is highly recommended that you use the HP Power Advisor in defining the "Right-Size" power supply for your needs. HP Power Advisor can be accessed at: www.hp.com/go/hppoweradvisor.

NOTE: The 80 PLUS program is a unique forum that unites electric utilities, the computer industry, and consumers in an effort to bring energy efficient technology solutions to the marketplace. 80 Plus independently tests power supply efficiency and publicly posts the results on 80Plus.org.

Redundant Power: Optional (1 + 1 redundant) power supplies can be purchased through power supply option kits (see Power Supplies for part numbers).

NOTE: Power Specification and Technical Content for supported power supplies can be found at: http://h18000.www1.hp.com/products/quickspecs/14209 div/14209 div.html

System Fans

One of the following depending on Model

(4) hot plug, redundant fans plus louvers

Fan Redundancy is standard in performance model. Four fans, PCIe baffles plus fan louvers are required for fan redundancy.

(3) hot plug, non-redundant fans

For fan redundancy in entry and base models, the HP Hot Plug Redundant Fan Kit (659486-B21) must be purchased. HP Hot Plug Redundant Fan Kit includes 4th fan, PCle baffles and fan louvers.



Standard Features

Operating Systems and Microsoft Windows Server Virtualization Software Canonical Ubuntu **Support for ProLiant** Servers

Red Hat Enterprise Linux (RHEL)

SUSE Linux Enterprise Server (SLES)

Solaris **VMware**

Citrix XenServer

NOTE: For more information on HP's Certified and Supported ProLiant Servers for OS and Virtualization Software and latest listing of software drivers available for your server, please visit our Support Matrix at: http://www.hp.com/go/ossupport and our driver download page http://www.hp.com/support/ML350pGen8

Graphics

Integrated Matrox G200 video standard

- 1280 x 1024 (32 bpp)
- 1920 x 1200 (16 bpp)

HP iLO 4 On System Management Memory

- 16 MB Flash
- 256 MB DDR 3 with ECC (112 MB after ECC and video)

Form Factor

Tower or Rack (5U)

On System Management

HP iLO Management Engine

HP iLO Management Engine is a comprehensive set of embedded management features supporting the complete lifecycle of the server, from initial deployment, through ongoing management, to service alerting and remote support. HP iLO Management Engine comes standard on all HP ProLiant Gen8 servers. The HP iLO Management Engine portfolio includes:

- **HP iLO**: The HP iLO (Integrated Lights-Out) management processor is the core foundation for the HP iLO Management **Engine**
- HP Agentless Management: Provides built in server health monitoring and alerting capability without OS agents, that starts working the moment a power cord and an Ethernet cable are connected.
- HP Active Health System: Always on, continuous monitoring for increased stability and shorter downtimes; 100% configuration history; Health and service alerts and easy export and upload to Service and Support.
- HP Intelligent Provisioning: Lets customers provision and configure a single server without any separate media. No more SmartStart CDs or Smart Update Firmware DVD are needed.
 - O To start Intelligent Provisioning:
 - Press the F10 key during the ProLiant Gen8 server boot process (also known as power on self-test or POST).
 - Please go to the Intelligent Provisioning website at:



Standard Features

- www.hp.com/go/intelligentprovisioning for additional information and to view usage videos.
- Use the Service Pack for ProLiant (SPP) at: www.hp.com/go/spp to get firmware and software updates.
- HP iLO Mobile App: Enables the ability to access, deploy, and manage your server anytime from anywhere from select smartphones and mobile devices. For additional information please visit: www.hp.com/go/ilo/mobileapp

NOTE: For more information, visit: http://www.hp.com/go/ilo or HP iLO Management Engine technologies whitepaper

HP Insight Management HP Service Pack for ProLiant (SPP)

HP Service Pack for ProLiant (SPP) and HP Smart Update Manager (HP SUM) provide a comprehensive approach to firmware and system software maintenance. Together they provide better operating stability and ensure maximum uptime. The SPP will be updated at a predictable cadence, typically coinciding with new HP server hardware launches. By enabling firmware to be updated online and integrating firmware and system software updates in one operation, HP SUM and the SPP offer faster updates of individual servers and dramatically faster updates of entire BladeSystem enclosures. Further improving system uptime and stability is the fact that HP provides 12 months of support for each Service Pack for ProLiant release.

The user experience around HP SUM and the SPP has been improved in several ways, starting with the web download. A single web page provides access to a single download containing both the latest version of HP SUM and the latest SPP. Optional smaller subsets with only specific types of servers or specific operating systems are offered to save on download time. The HP SUM application provides a straightforward, intuitive user interface that guides the user through the steps of discovery, analyses and update, providing comprehensive information on available updates, criticality and interdependencies. This information is also available in reports. By providing the option of multiple local or shared repositories which can be easily updated from hp.com, HP SUM provides the tools to optimize stability and consistency throughout the company. While HP SUM and the SPP recommend the combinations of firmware and system software that HP has found to be the best practice, the application gives customers the flexibility to set their own specific baseline.

The Service Pack for ProLiant has been rigorously tested with specific attention for interaction between firmware, drivers and agents both within the server as well as in interaction with the BladeSystem enclosure components (Onboard Administrator and Virtual Connect). This testing ensures the highest quality as well as providing the input for HP SUM to deploy updates taking into account all interdepencies, when determining the correct updates and order of update deployment.

NOTE: The Service Pack for ProLiant (which includes HP SUM) can be downloaded from www.hp.com/go/spp/download. More information can be found: http://www.hp.com/go/SmartUpdate, www.hp.com/go/spp and



Standard Features

http://www.hp.com/go/hpsum

HP StoreVirtual VSA

HP StoreVirtual VSA allows you to create fully featured shared storage on a VMware vSphere or Microsoft Hyper-V virtualized server. This server model starting November 2013, includes a limited license for HP StoreVirtual VSA software with 1TB of capacity. To download the license key and StoreVirtual VSA software, visit: www.hp.com/go/unlockVSA.

NOTE: You will need your server serial number in order to complete the registration form. Fully functional, capacity-based licenses are available in 4TB, 10TB, and 50TB sizes. For more information and access to the 60-day free trial, visit: www.hp.com/go/tryVSA

Security

Power-on password
Setup password
Serial interface control
Power switch security
Administrator's password

Warranty

This product is covered by a global limited warranty and supported by HP Services and a worldwide network of HP Authorized Channel Partners resellers. Hardware diagnostic support and repair is available for three years from date of purchase. Support for software and initial setup is available for 90 days from date of purchase. Enhancements to warranty services are available through HP Care Pack services or customized service agreements. Hard drives have either a one year or three year warranty; refer to the specific hard drive QuickSpecs for details.

NOTE: Server Warranty includes 3-Year Parts, 3-Year Labor, 3-Year Onsite support with next business day response. Warranty repairs may be accomplished through the use of Customer Self Repair (CSR) parts. These parts fall into two categories: 1) Mandatory CSR parts are designed for easy replacement. A travel and labor charge will result when customers decline to replace a Mandatory CSR part; 2) Optional CSR parts are also designed for easy replacement but may involve added complexity. Customers may choose to have HP replace Optional CSR parts at no charge. Additional information regarding worldwide limited warranty and technical support is available at: http://h18004.www1.hp.com/products/servers/platforms/warranty/index.html



Optional Features

HP Insight Management HP Insight Control

HP Insight Control, a product option, delivers essential infrastructure management that can help save time and money by making it easy to deploy, migrate, monitor, remote control, and optimize your IT infrastructure through a single, simple management console. HP Insight Control also supports Location and Power Discovery Services to automate many configuration, asset tracking, and power management tasks to speed implementation and prevent downtime. For more information, see http://www.hp.com/go/insightcontrol.

HP Insight Control includes one year of 24 x 7 HP Software Technical Support and Update Service ensuring rapid access to HP support staff and proactive delivery of software updates. For more information about this service, see: http://www.hp.com/services/insight.

HP iLO Advanced

HP Integrated Lights-Out Advanced License a product option, providing smart remote server management without compromise. iLO Advanced unlocks the full set of remote administration functionality for all HP ProLiant servers by activating the full Virtual Keyboard Video and Mouse remote console, multi-user collaboration, console record and replay, GUI-based and scripted virtual media and virtual folders, and enhanced security and power management functionality. For more information, see: http://www.hp.com/go/iloadvanced

HP Matrix Operating Environment

The HP Matrix Operating Environment (Matrix OE) for ProLiant and Integrity servers is an integrated command center that helps you instantly adjust to dynamic business demands. This advanced infrastructure management software lets you reduce the cost of common data center tasks by up to 40 percent while keeping pace with your changing business.

The HP Matrix OE includes the automated provisioning, optimization, and recovery management capabilities for HP CloudSystem Matrix, the ideal platform for private cloud and Infrastructure as a Service (laaS).

NOTE: For more information, visit: http://www.hp.com/go/matrixoe

High Performance Clusters

HP Cluster Platforms

HP Cluster Platforms are specifically engineered, factory-integrated largescale ProLiant clusters optimized for High Performance Computing, with a choice of servers, networks and software. Operating system options include specially priced offerings for Red Hat Enterprise Linux and SUSE Linux Enterprise Server, as well as Microsoft Windows HPC Server. A Cluster Platform Configurator simplifies ordering.

http://www.hp.com/go/clusters.

HP HPC Interconnects

High Performance Computing (HPC) interconnect technologies are available for this server as part of the HP Cluster Platform portfolio. These high-speed InfiniBand and Gigabit interconnects are fully supported by HP when integrated within an HP cluster. Flexible, validated solutions can be defined with the help of configuration tools.

http://www.hp.com/techservers/clusters/ucp/index.html



Optional Features

HP Insight Cluster Management Utility

HP Insight Cluster Management Utility (CMU) is an HP-licensed and HP-supported suite of tools that are used for lifecycle management of hyperscale clusters of Linux ProLiant systems. CMU includes software for the centralized provisioning, management and monitoring of nodes. CMU makes the administration of clusters user friendly, efficient, and effective. http://www.hp.com/go/cmu

Storage Software

Whether you need to solve a specific data protection, archiving, or storage command and control challenge, or deliver on strategic consolidation, compliance, or continuity initiatives, look no further than HP storage software. Our storage software helps you reduce costs, simplify storage infrastructure, protect vital assets and respond faster to business opportunities.

Storage software that gets the job done:

Data Protection and Recovery Software

Whether you're a large enterprise or a smaller business, HP data protection and recovery software will cost-effectively protect you against disaster and ensure business continuity.

• Data Archive and Migration Software

HP's storage software enables you to comply with data retention and retrieval requirements, improve application performance, and reduce costs by efficiently migrating infrequently accessed or less valuable data to lower cost storage.

Storage Resource Management Software (SRM)

HP's storage resource management software reduces operational costs and provides the command and control foundation you need to efficiently manage and visualize your physical and virtual environments.

• Data Replication Software

HP offers array-based and host-based replication software for use in disaster recovery, testing, application development and reporting.

Storage Device Management Software

Maximize your investment in HP storage and networking with software that enables hardwarespecific configuration, performance tuning and connectivity management.

HP StoreVirtual VSA

With HP StoreVirtual VSA you can use the power of virtualization to turn a set of heterogeneous and disconnected physical disk drives in your servers and storage devices into a single pool of logical storage capacity.

NOTE: For more information available Storage Software including QuickSpecs, please see: www.hp.com/go/storage/software.

HP Insight Online

HP Insight Online is a new addition to the HP Support Center for one stop, secure access to product and HP support information personalized to your IT environment. Insight Online can automatically display devices remotely monitored by HP Insight Remote Support. With Insight Online's easy navigation you can efficiently track your IT support contracts and device status from anywhere and at any time. www.hp.com/go/insightonline



Optional Features

HP Proactive Insight experience

Prevent problems with innovative, automated monitoring tools and proactive services. The HP Proactive Insight experience consists of using Insight Online, Insight Remote Support, and Proactive Care Support Service as one integrated solution. The Proactive Insight experience provides you with expert advice and personalized, cloud-based automated IT support, helping to prevent unplanned down time and solve problems quickly. For more information, visit: www.hp.com/go/proactiveinsightexperience

Factory Express Portfolio for Servers and Storage

HP Factory Express offers configuration, customization, integration and deployment services for HP servers and storage products. Customers can choose how their factory solutions are built, tested, integrated, shipped and deployed.

Factory Express offers service packages for simple configuration, racking, installation, complex configuration and design services as well as individual factory services, such as image loading, asset tagging, and custom packaging. HP products supported through Factory Express include a wide array of servers and storage: HP Integrity, HP ProLiant, HP ProLiant Server Blades, HP BladeSystem, HP 9000 servers as well as the MSAxxxx, VA7xxx, EVA, XP, rackable tape libraries and configurable network switches.

For more information on Factory Express services for your specific server model please contact your sales representative or go to: http://www.hp.com/go/factory-express

HP Simple Configurator SCE is a guided self-service tool to help sales and non-technical people provide customers with initial configurations in 3 to 5 minutes. You may then send the configuration on for configuration help, or use in your existing ordering processes. If you require "custom" rack configuration or configuration for products not available in SCE, please contact HP's Customer Business Center or an Authorized Partner for assistance. http://www.hp.com/products/configurator

HP Computation and Graphics Accelerators

Each ML350p server will accommodate up to three NVIDIA Quadro and Tesla GPU PCIe cards for high-end QUADRO® graphics and accelerated high performance computing.



Service and Support

Service and Support

HP Technology Services for Industry Standard Servers

Capitalizing on HP ProLiant server and HP BladeSystem capabilities requires a service partner who understands your increasingly complex business technology environment. That's why it makes sense to team up with the people who know HP infrastructure hardware and software best - the experienced professionals at HP Services.

Protect your business beyond warranty with HP Care Pack Services

HP Care Pack services offer complete care and support expertise with committed response choices designed to meet your IT and business needs.

HP Foundation Care services offer scalable reactive support-packages for HP industry-standard servers and software. You can choose the type and level of service that is most suitable for your IT and business needs. HP Proactive Care delivers high levels of system availability through proactive service management and advanced technical response

Optimized Care

Supports maintaining servers at optimum performance availability

3-Year HP 6 hour Call to Repair Response, Proactive Care*

Combined reactive and proactive support for hardware and software helping optimize your systems and delivering high levels of availability through proactive service management and advanced technical response. Hardware problem resolution to return the hardware in operating condition within 6 hours of the initial service request. A Technical Account Manager, as your single point of contact, will own your call or issue end to end until resolved.

http://h20195.www2.hp.com/v2/GetPDF.aspx/4AA3-8855EEE.pdf

HP ProLiant Server Hardware Installation

Provides for the basic hardware installation of HP branded servers, storage devices and networking options to assist you in bringing your new hardware into operation in a timely and professional manner http://h20195.www2.hp.com/V2/GetPDF.aspx/5981-9356EN.pdf

Standard Care

Service recommendation that maintains high level of server availability

3-Year HP 24x7 4 hour response, Proactive Care Service*

This service gives you combined reactive and proactive support including rapid access to our Advanced Solution Center to manage and prevent problems and a Technical Support Specialist with a broad level of technical knowledge that will engage with additional technical expertise as needed from HP's vast global resources.

http://h20195.www2.hp.com/v2/GetPDF.aspx/4AA3-8855EEE.pdf

HP ProLiant Server Hardware Installation

Provides for the basic hardware installation of HP branded servers, storage devices and networking options to assist you in bringing your new hardware into operation in a timely and professional manner http://h20195.www2.hp.com/V2/GetPDF.aspx/5981-9356EN.pdf

Related Services

HP Proactive Care Personalized Support - Environmental Option

The Personalized Support option provides an assigned Account Support Manager who can bring best practices from across the industry plus extra technical skills to your IT team. This option is only available as an add-on to HP Proactive Care Support.

HP Proactive Select Service

Provides a flexible way to purchase HP best-in-class consultancy and technical services. You can buy Proactive Select Service Credits when you purchase your hardware and then use the credits over the next 12 months. http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA2-3842ENN.pdf

Additional HP Care Pack services can be found at: http://www.hp.com/go/cpc



Service and Support

Insight Online/Insight Remote Support

HP Insight Remote Support provides 24 X 7 remote monitoring, proactive notifications, and problem resolution. This comes at no additional cost with your HP solution*. Learn more about Insight Remote Support http://www.hp.com/go/insightremotesupport and Insight Online http://www.hp.com/go/insightonline

* Insight Remote Support is a prerequisite for Proactive Care.

Parts and Material

HP will provide HP-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by HP due to malfunction.

For more information

To learn more on HP ProLiant servers, please contact your HP sales representative or HP Authorized ServiceOne Channel Partner. Or visit: http://www.hp.com/services/proliant



Pre-configured Models

NOTE: For the Standard Features shipped in the "Factory Integrated Models", please see the "Configuration Information -Factory Integrated Models" section.

NOTE: Pre-configured models ship with the configurations below. Options can be selected from the Core or Additional options section of this QuickSpecs.

NOTE: HP does not allow factory integration of options into pre-configured models. Any additional options purchased will be shipped separately.

NOTE: If you desire a custom configuration please see "Configuration Information - Factory Integrated Models" section of this QuickSpecs.

NOTE: All Pre-configured Models come populated with some hard drive blanks installed. Should the customer need additional hard drive blanks, they can order more using either P/N 666987-B21: HP SFF Gen8 Hard Drive Blank Kit or P/N 666986-B21: HP LFF Gen8 Hard Drive Blank Kit.

NOTE: Not all models are available in all regions. Check with your local country HP offices for availability.

Entry Models

E5-2600 v2 series Processors

HP ProLiant ML350p Gen8 E5-2609v2 1P 4GB-R P420i/ZM 6 LFF 460W PS Server 736947-xx1

Processor

(1) Intel® Xeon® E5-2609 v2 (2.50GHz/4-core/10MB/6.4GT-s QPI/80W)

Processor

Cache Memory

10MB (1 x 10MB) L3

Memory 4GB (1x4GB) PC3L-12800R (DDR3-1600LV) Registered DIMMS

HP 1Gb Ethernet 4-port 331i Adapter

NOTE: 11 DIMM slots available (23 if second processor is purchased).

Network Controller

Storage Controller HP Smart Array P420i/Zero Memory Controller

Hard Drive None ship standard; includes 5 LFF hard drive blanks **Internal Storage** (6) Hot plug LFF SAS/SATA HDD bays; upgradable to (18)

Optical Drive HP Half-Height SATA DVD-ROM Optical Drive

Power Supply (1) HP 460W Common Slot Gold Hot Plug Power Supply

Fans 3 hot plug, non-redundant fans

Accessories USB Keyboard and Mouse ship standard

NOTE: EURO (-421) Models excludes the keyboard.

Management HP iLO Management Engine (standard)

Optional: HP Insight Control

Form Factor Tower (5U)

Warranty Server Warranty includes 3-Year Parts, 3-Year Labor, 3-Year Onsite

support with next business day response

E5-2600 series Processors

HP ProLiant ML350p Gen8 E5-2609 1P 4GB-R P420i Hot Plug 6 LFF 460W PS Entry Svr 646675-xx1

Processor

(1) Intel® Xeon® E5-2609(2.40GHz/4-core/10MB/6.4GT-s QPI/80W)

Processor

Cache Memory 10MB (1 x 10MB) L3

Memory 4GB (1x4GB) PC3L-10600R (DDR3-1333) Registered DIMMS

NOTE: 11 DIMM slots available (23 if second processor is purchased).

Network Controller HP 1Gb Ethernet 4-port 331i Adapter

Storage Controller HP Smart Array P420i/Zero Memory Controller

Hard Drive None ship standard; includes 5 LFF hard drive blanks **Internal Storage** (6) Hot plug LFF SAS/SATA HDD bays; upgradable to (18)

Optical Drive HP Half-Height SATA DVD-ROM Optical Drive



Pre-configured Models

Power Supply (1) HP 460W Common Slot Gold Hot Plug Power Supply

Fans 3 hot plug, non-redundant fans

Accessories USB Keyboard and Mouse ship standard

NOTE: EURO (-421) Models excludes the keyboard.

Management HP iLO Management Engine (standard)

Optional: HP Insight Control

Form Factor Tower (5U)

Warranty Server Warranty includes 3-Year Parts, 3-Year Labor, 3-Year Onsite

support with next business day response

Base Models

E5-2600 v2 series Processors

HP ProLiant ML350p Gen8 E5-2620v2 1P

8GB-R P420i/512 FBWC 8 SFF 460W PS Server

736958-xx1

Processor

(1) Intel® Xeon® E5-2620 v2 (2.1GHz/6-core/15MB/7.2GT-s QPI/80W,

DDR3-1333, HT, Turbo2- 3/3/4/4/5/5) Processor

Cache Memory 15MB (1 x 15MB) L3

Memory 8GB (1x8GB) PC3L-12800R (DDR3-1600LV) Registered DIMMS

NOTE: 11 DIMM slots available (23 if second processor is purchased).

Network Controller HP 1Gb Ethernet 4-port 331i Adapter

Storage Controller HP Smart Array P420i/512M FBWC Controller (RAID

0/1/1+0/5/5+0/6/6+0)

Hard Drive None ship standard; includes 7 SFF hard drive blanks
Internal Storage (8) Hot plug SFF SAS/SATA HDD bays; upgradable to (24)

Optical Drive HP Half-Height SATA DVD-RW Optical Drive

Power Supply (1) HP 460W Common Slot Gold Hot Plug Power Supply

Fans 3 hot plug, non-redundant fans

Accessories USB Keyboard and Mouse ship standard

NOTE: EURO (-421) Models excludes the keyboard.

Management HP iLO Management Engine (standard)

Optional: HP Insight Control

Form Factor Tower (5U)

Warranty Server Warranty includes 3-Year Parts, 3-Year Labor, 3-Year Onsite

support with next business day response

E5-2600 series Processors

HP ProLiant ML350p Gen8 E5-2620 1P 8GB-R

P420i Hot Plug 8 SFF 460W PS Base Svr

646676-xx1

Processor

(1) Intel® Xeon® E5-2620 (2.0GHz/6-core/15MB/7.2GT-s QPI/95W,

DDR3-1333, HT, Turbo2- 3/3/4/4/5/5) Processor

Cache Memory 15MB (1 x 15MB) L3

Memory 8GB (2x4B) PC3L-10600R (DDR3-1333) Registered DIMMS

NOTE: 10 DIMM slots available (22 if second processor is purchased).

Network Controller HP 1Gb Ethernet 4-port 331i Adapter

Storage Controller HP Smart Array P420i/512M FBWC Controller (RAID

0/1/1+0/5/5+0/6/6+0)

Hard Drive None ship standard; includes 7 SFF hard drive blanks
Internal Storage (8) Hot plug SFF SAS/SATA HDD bays; upgradable to (24)



Pre-configured Models

Optical Drive HP Half-Height SATA DVD-ROM Optical Drive

Power Supply (1) HP 460W Common Slot Gold Hot Plug Power Supply

Fans 3 hot plug, non-redundant fans

Accessories USB Keyboard and Mouse ship standard

NOTE: EURO (-421) Models excludes the keyboard.

Management HP iLO Management Engine (standard)

Optional: HP Insight Control

Form Factor Tower (5U)

Warranty Server Warranty includes 3-Year Parts, 3-Year Labor, 3-Year Onsite

support with next business day response

HP ProLiant ML350p Gen8 E5-2630 1P 8GB-R P420i Hot Plug 8 SFF 750W PS Base Svr 646677-xx1 **Processor** (1) Intel® Xeon® E5-2630 (2.30GHz/6-core/15MB/7.2GT-s QPI/95W,

DDR3-1333, HT, Turbo2- 3/3/4/4/5/5) Processor

Cache Memory 15MB (1 x 15MB) L3

Memory 8GB (2x4GB) PC3L-10600R (DDR3-1333) Registered DIMMS

NOTE: 10 DIMM slots available (22 if second processor is purchased).

Network Controller HP 1Gb Ethernet 4-port 331i Adapter

Storage Controller HP Smart Array P420i/1G FBWC Controller (RAID 0/1/1+0/5/5+0/6/6+0)

Hard Drive None ship standard; includes 7 SFF hard drive blanks
Internal Storage (8) Hot plug SFF SAS/SATA HDD bays; upgradable to (24)

Optical Drive HP Half-Height SATA DVD-RW Optical Drive

Power Supply (1) HP 750W Common Slot Platinum Plus Hot Plug Power Supply

Management HP iLO Management Engine (standard)

Optional: HP Insight Control

Fans 3 hot plug, non-redundant fans

Form Factor Rack (5U)

Warranty Server Warranty includes 3-Year Parts, 3-Year Labor, 3-Year Onsite

support with next business day response

Performance Models

HP ProLiant ML350p Gen8 E5-2650 2P 16GB-R P420i Hot Plug 8 SFF 750W PS ES Server 678237-xx1

Processor

(2) Intel® Xeon® E5-2650 (2.0GHz/8-core/20MB/8GT-s QPI/95W, DDR3-

1600, HT, Turbo2- 4/4/5/5/5/7/8/8) Processors

Cache Memory 20MB (1 x 20MB) L3

Memory 16GB (4x4GB) PC3L-10600R (DDR3-1333) Registered DIMMS

NOTE: 20 DIMM slots available.

Network Controller HP 1Gb Ethernet 4-port 331i Adapter

Storage Controller HP Smart Array P420i/2G FBWC Controller (RAID 0/1/1+0/5/5+0/6/6+0)

Hard Drive None ship standard; includes 7 SFF hard drive blanks
Internal Storage (8) Hot plug SFF SAS/SATA HDD bays; upgradable to (24)

Optical Drive HP Half-Height SATA DVD-RW Optical Drive

Power Supply (2) HP 750W Common Slot Platinum Plus Hot Plug Power Supply

Fans 4 hot plug, redundant fans plus louvers



Pre-configured Models

Accessories USB Keyboard and Mouse ship standard

NOTE: EURO (-421) Models excludes the keyboard.

Management HP iLO Management Engine (standard)

HP Insight Control Standard

Energy Star Meets Energy Star requirements

Form Factor Tower (5U)

Warranty Server Warranty includes 3-Year Parts, 3-Year Labor, 3-Year Onsite

support with next business day response

Performance Models

NOTE: These Models are Energy Star Certified.

E5-2600 v2 series Processors

HP ProLiant ML350p Gen8 E5-2650v2 2P

16GB-R P420i/2GB

FBWC 8 SFF 750W RPS

Server 736968-xx1

Processor

Cache Memory

Memory

Hard Drive

20MB (1 x 20MB) L3

16GB (2x8GB) PC3-14900R (DDR3-1866) Registered DIMMS

DDR3-1333, HT, Turbo2-3/3/4/4/5/5) Processors

(2) Intel® Xeon® E5-2650 v2 (2.60GHz/8-core/20MB/7.2GT-s QPI/95W,

NOTE: 20 DIMM slots available.

Network Controller

Storage Controller

HP 1Gb Ethernet 4-port 331i Adapter HP Smart Array P420i/2G FBWC Controller (RAID 0/1/1+0/5/5+0/6/6+0)

None ship standard; includes 7 SFF hard drive blanks (8) Hot plug SFF SAS/SATA HDD bays; upgradable to (24)

Internal Storage
Optical Drive

HP Half-Height SATA DVD-RW Optical Drive

Power Supply

(2) HP 750W Common Slot Platinum Plus Hot Plug Power Supplies

Fans

4 hot plug, redundant fans plus louvers
USB Keyboard and Mouse ship standard

Accessories

NOTE: EURO (-421) Models excludes the keyboard.

Management

HP iLO Management Engine (standard)

HP Insight Control Standard

Energy Star

Meets Energy Star requirements

Form Factor

Tower(5U)

Warranty

Server Warranty includes 3-Year Parts, 3-Year Labor, 3-Year Onsite

support with next business day response

HP ProLiant ML350p Gen8 E5-2640v2 2P 16GB-R P420i/2GB FBWC 8 SFF 750W RPS

Server 736967-xx1

Processor

(2) Intel® Xeon® E5-2640 v2 (2.0GHz/8-core/20MB/7.2GT-s QPI/95W, DDR3-1600, HT, Turbo2- 3/3/3/3/4/5) Processors

Cache Memory 20MB (1 x 20MB) L3

Memory 16GB (2x8GB)

16GB (2x8GB) PC3L-12800R (DDR3-1600LV) Registered DIMMS

NOTE: 20 DIMM slots available.

Network Controller

HP 1Gb Ethernet 4-port 331i Adapter

Storage Controller

HP Smart Array P420i/2G FBWC Controller (RAID 0/1/1+0/5/5+0/6/6+0)

Hard Drive Internal Storage None ship standard; includes 7 SFF hard drive blanks

Optical Drive

(8) Hot plug SFF SAS/SATA HDD bays; upgradable to (24)

Optical Drive

HP Half-Height SATA DVD-RW Optical Drive

Power Supply

(2) HP 750W Common Slot Platinum Plus Hot Plug Power Supply



Pre-configured Models

4 hot plug, redundant fans plus louvers **Fans** Management HP iLO Management Engine (standard)

HP Insight Control Standard

Energy Star Meets Energy Star requirements

Form Factor Rack (5U)

Server Warranty includes 3-Year Parts, 3-Year Labor, 3-Year Onsite Warranty

support with next business day response

E5-2600 series Processors

HP ProLiant ML350p Gen8 E5-2640 2P 16GB-R P420i Hot Plug 8 SFF Cache Memory 750W PS Perf Svr 646678-xx1

(2) Intel® Xeon® E5-2640 (2.50GHz/6-core/15MB/7.2GT-s QPI/95W, **Processor** DDR3-1333, HT, Turbo2- 3/3/4/4/5/5) Processors

15MB (1 x 15MB) L3

Memory 16GB (4x4GB) PC3L-10600R (DDR3-1333) Registered DIMMS

NOTE: 20 DIMM slots available.

HP 1Gb Ethernet 4-port 331i Adapter **Network Controller**

Storage Controller

xx=AA

HP Smart Array P420i/2G FBWC Controller (RAID 0/1/1+0/5/5+0/6/6+0)

PRC

Hard Drive None ship standard; includes 7 SFF hard drive blanks **Internal Storage** (8) Hot plug SFF SAS/SATA HDD bays; upgradable to (24)

Optical Drive HP Half-Height SATA DVD-RW Optical Drive

Power Supply (2) HP 750W Common Slot Platinum Plus Hot Plug Power Supplies

4 hot plug, redundant fans plus louvers **Fans** HP iLO Management Engine (standard) Management

HP Insight Control Standard

Energy Star Meets Energy Star requirements

Form Factor Rack(5U)

Server Warranty includes 3-Year Parts, 3-Year Labor, 3-Year Onsite Warranty

support with next business day response

Country Code Key

	Tower Code Key	Rack Code Key
xx=00	US	US
xx=01	Australia	N/A
xx=03	UK	N/A
xx=04	Germany	N/A
xx=05	France	N/A
xx=20	Brazil	N/A
xx=29	Japan	Japan
xx=37	APD	APD
xx=42	Europe NOTE: EURO (-421) Models excludes the keyboard.(Excludes USB Keyboard)	Europe



PRC

Configuration Information - Factory Integrated Models

NOTE: This section lists some of the steps required to configure a Factory Integrated Model. To ensure only valid configurations are ordered, HP recommends the use of an HP approved configurator. Contact your local sales representative for information on configurable product offerings and requirements.

NOTE: Factory Integrated Models must start with a CTO Server.

NOTE: FIO indicates that this option is only available as a factory installable option.

NOTE: All Factory Integrated Models will be populated with sufficient hard drive blanks based on the number of initial hard drives ordered with the server.

Step 1: Base Configuration (choose one of the following configurable models)

HP Models ML350p Gen8 Tower Models

HP ProLiant ML350p Gen8 Hot Plug 8 SFF Configure-to-order Tower Server

652065-B21

Includes:

HP 1Gb Ethernet 4-port 331i Adapter HP Smart Array P420i Controller

Eight (8) Hot-Plug (SFF) SAS/SATA Drive Bays

Seven (7) HDD blanks Ten (10) USB ports

Eight (8) PCIe 3.0 slots (3x16, 1x8, 4x4), One (1) PCIe 2.0 slot (1x4)

USB Keyboard & Mouse (optional) HP iLO Management Engine (standard)

Tower (5U) form factor SID Module (optional)

HP ProLiant ML350p Gen8 Hot Plug 6 LFF Configure-to-order Tower Server

652066-B21

Includes:

HP 1Gb Ethernet 4-port 331i Adapter

HP Smart Array P420i Controller

Six (6) Hot-Plug (LFF) SAS/SATA Drive Bays

Five (5) HDD blanks Ten (10) USB ports

Eight (8) PCle 3.0 slots (3x16, 1x8, 4x4), One (1) PCle 2.0 slot (1x4)

USB Keyboard & Mouse (optional)
HP iLO Management Engine (standard)

Tower (5U) form factor SID Module (optional)

ML350p Gen8 Rack Models

HP ProLiant ML350p Gen8 Hot Plug 8 SFF Configure-to-order Rack Server

652063-B21

Includes:

HP 1Gb Ethernet 4-port 331i Adapter HP Smart Array P420i Controller

Eight (8) Hot-Plug (SFF) SAS/SATA Drive Bays

Seven (7) HDD blanks

Ten (10) USB ports Eight (8) PCle 3.0 slots (3x16, 1x8, 4x4), One (1) PCle .2.0 slot (1x4)

HP iLO Management Engine (standard)

Rack (5U) form factor

Sliding Rail Kit

SID module (standard)

HP ProLiant ML350p Gen8 Hot Plug 6 LFF Configure-to-order Rack Server

652064-B21

Includes:

HP Embedded 1 Gb Ethernet 4-port 331i Adapter



Configuration Information - Factory Integrated Models

Embedded HP Smart Array P420i Controller Six(6) Hot-Plug (LFF) SAS/SATA Drive Bays

Five(5) HDD blanks Ten (10) USB ports

Eight (8) PCle 3.0 slots (3x16, 1x8, 4x4), One (1) PCle 2.0 slot (1x4)

HP iLO Management Engine (standard)

Rack (5U) form factor Sliding Rail Kit SID module (standard)

Processor Kit

Step 2: Choose Required Options (only one of the following from each list unless otherwise noted)

HP Processors

NOTE: If two processors are desired, select one xxxxxx-L21 and one xxxxxx-B21

Entry Processors - E5-2600 v2 series Processors

NOTE: All support up to 1333MHz memory speeds.

HP ML350p Gen8 Intel® Xeon® E5-2609v2 (2.5GHz/4-core/10MB/80W) FIO 722284-L21
Processor Kit

HB ML350p Gen8 Intel® Xeon® E5-2603v3 (1.8CHz/4-core/10MB/80W) FIO 722284-L21

HP ML350p Gen8 Intel® Xeon® E5-2603v2 (1.8GHz/4-core/10MB/80W) FIO 722285-L21 Processor Kit

Base Processors - E5-2600 v2 series Processors

NOTE: All support up to 1600 MHz DDR3 memory speeds.

HP ML350p Gen8 Intel® Xeon® E5-2640v2 (2.0GHz/8-core/20MB/95W) FIO 709491-L21 Processor Kit

HP ML350p Gen8 Intel® Xeon® E5-2630v2 (2.6GHz/6-core/15MB/80W) FIO 709492-L21 Processor Kit

HP ML350p Gen8 Intel® Xeon® E5-2620v2 (2.1GHz/6-core/15MB/80W) FIO 709493-L21

Processor Kit

HP ML350p Gen8 Intel® Xeon® E5-2630Lv2 (2.4GHz/6-core/15MB/60W) FIO 722287-L21

Performance Processors - E5-2600 v2 series Processors

NOTE: All support up to 1866MHz DDR3 memory speeds

HP ML350p Gen8 Intel® Xeon® E5-2697v2 (2.7GHz/12-core/30MB/130W) FIO 722301-L21 Processor Kit

HP ML350p Gen8 Intel® Xeon® E5-2690v2 (3.0GHz/10-core/25MB/130W) FIO 709486-L21 Processor Kit

HP ML350p Gen8 Intel® Xeon® E5-2680v2 (2.8GHz/10-core/25MB/115W) FIO 709487-L21 Processor Kit

HP ML350p Gen8 Intel® Xeon® E5-2670v2 (2.5GHz/10-core/25MB/115W) FIO 709488-L21 Processor Kit

HP ML350p Gen8 Intel® Xeon® E5-2667v2 (3.3GHz/8-core/25MB/130W) FIO 722303-L21 Processor Kit

HP ML350p Gen8 Intel® Xeon® E5-2650v2 (2.6GHz/8-core/20MB/95W) FIO 709490-L21 Processor Kit

HP ML350p Gen8 Intel® Xeon® E5-2643v2 (3.5GHz/6-core/25MB/130W) FIO 722304-L21 Processor Kit



Configuration Information - Factory Integrated Models

,	
HP ML350p Gen8 Intel® Xeon® E5-2637v2 (3.5GHz/4-core/15MB/130W) FIO Processor Kit	722305-L21
Entry Processors - E5-2600 series Processors	
NOTE: All support up to 1066MHz memory speeds.	000507104
HP ML350p Gen8 Intel® Xeon® E5-2609 (2.40GHz/4-core/10MB/80W) FIO Processor Kit	660597-L21
HP ML350p Gen8 Intel® Xeon® E5-2603 (1.8GHz/4-core/10MB/80W) FIO Processor Kit	660595-L21
Base Processors - E5-2600 series Processors	
NOTE: All support up to1333MHz DDR3 memory speeds.	
HP ML350p Gen8 Intel® Xeon® E5-2640 (2.5GHz/6-core/15MB/95W) FIO Processor Kit	660600-L21
HP ML350p Gen8 Intel® Xeon® E5-2630 (2.30GHz/6-core/15MB/95W) FIO Processor Kit	660599-L21
HP ML350p Gen8 Intel® Xeon® E5-2620 (2.0GHz/6-core/15MB/95W) FIO Processor Kit	660598-L21
HP ML350p Gen8 Intel® Xeon® E5-2630L (2.0GHz/6-core/15MB/60W) FIO Processor Kit	660607-L21
Performance Processors - E5-2600 series Processors	
NOTE: All support up to1600MHz DDR3 memory speeds.	
HP ML350p Gen8 Intel® Xeon® E5-2690 (2.9GHz/8-core/20MB/135W) FIO Processor Kit	660605-L21
HP ML350p Gen8 Intel® Xeon® E5-2680 (2.7GHz/8-core/20MB/130W) FIO	660604-L21
Processor Kit HP ML350p Gen8 Intel® Xeon® E5-2670 (2.6GHz/8-core/20MB/115W) FIO	660603-L21
Processor Kit	
HP ML350p Gen8 Intel® Xeon® E5-2667 (2.9GHz/6-core/15MB/130W) FIO Processor Kit	660608-L21
HP ML350p Gen8 Intel® Xeon® E5-2665 (2.4GHz/8-core/20MB/115W) FIO Processor Kit	660596-L21
HP ML350p Gen8 Intel® Xeon® E5-2660 (2.2GHz/8-core/20MB/95W) FIO Processor Kit	660602-L21
HP ML350p Gen8 Intel® Xeon® E5-2650 (2.0GHz/8-core/20MB/95W) FIO Processor Kit	660601-L21
HP ML350p Gen8 Intel® Xeon® E5-2650L (1.8GHz/8-core/20MB/70W) FIO Processor Kit	660606-L21
HP ML350p Gen8 Intel® Xeon® E5-2643 (3.3GHz/4-core/10MB/130W) FIO Processor Kit	678242-L21
HP ML350p Gen8 Intel® Xeon® E5-2637 (3.0GHz/2-core/5MB/80W) FIO Processor Kit	678244-L21
NOTE: HP memory from previous generation servers are not qualified or	
warranted with this HP ProLiant Server. HP SmartMemory is required to realize	
the memory performance improvements and enhanced functionality listed in this	
document for Gen8. For additional information, please see the HP SmartMemory QuickSpecs at:	
http://h18000.www1.hp.com/products/quickspecs/14225_div/14225_div.html	
NOTE: I RDIMM RDIMM and LIDIMMs are all distinct memory technologies and	

HP Memory

NOTE: LRDIMM, RDIMM and UDIMMs are all distinct memory technologies and cannot be mixed within a server. The majority of ProLiant Gen8 servers support RDIMM, UDIMM and LRDIMM.

Configuration Information - Factory Integrated Models

Registered DIMMs (RDIMMs) NOTE: The following memory is supported by the E5-2600 v	v2 series Processors.	
HP 4GB (1x4GB) Single Rank x4 PC3L-12800R (DDR3-160 11 Low Voltage Memory Kit	0) Registered CAS-	713981-B21
HP 4GB (1x4GB) Single Rank x4 PC3-14900R (DDR3-1866 Memory Kit) Registered CAS-13	708637-B21
HP 8GB (1x8GB) Dual Rank x4 PC3L-12800R (DDR3-1600) Low Voltage Memory Kit	Registered CAS-11	713983-B21
HP 8GB (1x8GB) Single Rank x4 PC3L-12800R (DDR3-160 11 Low Voltage Memory Kit	0) Registered CAS-	731765-B21
HP 8GB (1x8GB) Dual Rank x4 PC3-14900R (DDR3-1866) Memory Kit	Registered CAS-13	708639-B21
HP 8GB (1x8GB) Single Rank x4 PC3-14900R (DDR3-1866 Memory Kit) Registered CAS-13	731761-B21
HP 16GB (1x16GB) Dual Rank x4 PC3L-12800R (DDR3-16011 Low Voltage Memory Kit	00) Registered CAS-	713985-B21
HP 16GB (1x16GB) Dual Rank x4 PC3-14900R (DDR3-1866 13 Memory Kit	3) Registered CAS-	708641-B21
Registered DIMMs (RDIMMs)		
NOTE : The following memory is supported by the E5-2600 s		
HP 4GB (1x4GB) Single Rank x4 PC3L-10600R (DDR3-133 Low Voltage Memory Kit	3) Registered CAS-9	647893-B21
HP 4GB (1x4GB) Single Rank x4 PC3-12800R (DDR3-1600 Memory Kit) Registered CAS-11	647895-B21
HP 8GB (1x8GB) Dual Rank x4 PC3L-10600R (DDR3-1333) Low Voltage Memory Kit	Registered CAS-9	647897-B21
HP 8GB (1x8GB) Single Rank x4 PC3-12800R (DDR3-1600 Memory Kit) Registered CAS-11	647899-B21
HP 8GB (1x8GB) Dual Rank x4 PC3-12800R (DDR3-1600) Memory Kit	Registered CAS-11	690802-B21
HP 16GB (1x16GB) Dual Rank x4 PC3L-10600R (DDR3-1339 Low Voltage Memory Kit	33) Registered CAS-	647901-B21
HP 16GB (1x16GB) Dual Rank x4 PC3-12800R (DDR3-1600 11 Memory Kit	0) Registered CAS-	672631-B21
Unbuffered with ECC DIMMs (UDIMMs)		
NOTE: The following memory is supported by the E5-2600 v	/2 series Processors.	
HP 2GB (1x2GB) Single Rank x8 PC3L-12800E (DDR3-1600 11 Low Voltage Memory Kit	0) Unbuffered CAS-	713975-B21
HP 2GB (1x2GB) Single Rank x8 PC3-14900E (DDR3-1866) Memory Kit) Unbuffered CAS-13	708631-B21
HP 4GB (1x4GB) Dual Rank x8 PC3L-12800E (DDR3-1600) Low Voltage Memory Kit	Unbuffered CAS-11	713977-B21
HP 4GB (1x4GB) Dual Rank x8 PC3-14900E (DDR3-1866) UMemory Kit	Jnbuffered CAS-13	708633-B21
HP 8GB (1x8GB) Dual Rank x8 PC3L-12800E (DDR3-1600) Low Voltage Memory Kit	Unbuffered CAS-11	713979-B21
HP 8GB (1x8GB) Dual Rank x8 PC3-14900E (DDR3-1866) UMemory Kit	Jnbuffered CAS-13	708635-B21



1

1

1

1

1

1

1

1

QuickSpecs

Configuration Information - Factory Integrated Models

Unbuffered with ECC DIMMs (UDIMMs) NOTE: The following memory is supported by the E5-2600 series Processors.	
HP 2GB (1x2GB) Single Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory Kit	669320-B21
HP 2GB (1x2GB) Single Rank x8 PC3L-10600E (DDR3-1333) Unbuffered CAS-9 Low Voltage Memory Kit	647905-B21
HP 4GB (1x4GB) Dual Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory Kit	669322-B21
HP 4GB (1x4GB) Dual Rank x8 PC3L-10600E (DDR3-1333) Unbuffered CAS-9 Low Voltage Memory Kit	647907-B21
HP 8GB (1x8GB) Dual Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory Kit	669324-B21
HP 8GB (1x8GB) Dual Rank x8 PC3L-10600E (DDR3-1333) Unbuffered CAS-9 Low Voltage Memory Kit	647909-B21
Load Reduced DIMMs (LRDIMMs)	
NOTE: The following memory is supported by the E5-2600 v2 series Processors.	
HP 32GB (1x32GB) Quad Rank x4 PC3-14900L (DDR3-1866) Load Reduced CAS-13 Memory Kit	708643-B21
Load Reduced DIMMs (LRDIMMs)	
NOTE: The following memory is supported by the E5-2600 series Processors.	
HP 32GB (1x32GB) Quad Rank x4 PC3L-10600L (DDR3-1333) Load Reduced CAS-9 Low Voltage Memory Kit	647903-B21

NOTE: All DDR3 memory option kits consist of one DIMM per kit. For detailed memory configuration rules and guidelines, please use the Online DDR3 Memory Configuration Tool: www.hp.com/go/ddr3memory-configurator.

NOTE: Depending on the memory configuration and processor model, 1866MHz, 1600MHz, and 1333MHz memory may operate at a lower speed. Please see the see the "Memory" section later in this document and the Online Memory Configuration Tool for details at www.hp.com/go/ddr3memory-configurator.

HP Power Supplies

NOTE: Mixing of power supplies in the same server is not supported. All power supplies inside a server must be exactly the same model. Mixing Gold, Platinum, and Platinum Plus certified power supplies is not supported.

NOTE: Prior to making a power supply selection it is highly recommended that the HP Power Advisor is run to determine the right size power supply for your server configuration. The HP Power Advisor is located at: www.hp.com/go/hppoweradvisor

HP Common Slot Platinum Plus Power Supply Kits

NOTE: The following Power Supplies offer 94% Efficiency with support for Intelligent Power Discovery.

HP 460W Common Slot Platinum Plus Hot Plug Power Supply Kit	656362-B21	
HP 750W Common Slot Platinum Plus Hot Plug Power Supply Kit	656363-B21	
HP 1200W Common Slot Platinum Plus Hot Plug Power Supply Kit	656364-B21	
HP Common Slot Gold Power Supplies		
NOTE: The following Power Supplies offer up to 92% efficiency.		
HP 460W Common Slot Gold Hot Plug Power Supply Kit	503296-B21	
HP 750W Common Slot Gold Hot Plug Power Supply Kit	512327-B21	

HP Common Slot -48VDC Power Supplies



Configuration Information - Factory Integrated Models

HP 750W Common Slot -48VDC Hot Plug Power Supply Kit

636673-B21

NOTE: The HP 750W Common Slot -48VDC power supply does not ship with a power cable. It has been designed with a terminal block connection allowing for custom design of power cords by the user.

Enablement Kit

HP 4X1200W RPS FIO Enablement Kit

659487-B21

NOTE: This kit Requires the selection of either 2 x 1200W power supply kits or 4

x 1200w power supply kits.

Step 3: Choose Additional Factory Integratable Options (only one of the following from each list unless otherwise noted)

HP Graphics Options HP 3rd FIO Graphic Card Power Cable Kit 700835-B21

NOTE: This FIO kit only require when 3 graphic card order.

HP SID Module HP Systems Insight Display FIO Kit 660583-B21

NOTE: Provides health status for key components (for CTO Tower Models only,

standard in Rack Models)

HP Insight Software HP Insight Control including 1yr 24x7 Support ProLiant ML/DL/BL-bundle Single C6N36A

Server FIO License

HP Insight Control including 1yr 24x7 Support ProLiant ML/DL/BL-bundle FIO C6N36ABE

Electronic License

NOTE: The Electronic software license is available in EMEA only.

HP Storage Controller Optional Upgrade

HP 4GB Flash Backed Write Cache FIO Kit for P-series Smart Array Controllers 698537-B21

Step 4: Choose Additional Options for Factory Integration

NOTE: For additional options, please refer to the "Core Options" and "Additional Options" section below.



Core Options

NOTE: Some options ma	ay not be integrated at the factory. Contact your local sales representative for additional	l information.	
HP Unique Options	HP Hot Plug Redundant Fan Kit		
	HP Tower to Rack Conversion Tray Kit	659488-B21	
	HP Security Bezel Kit	660584-B21	
	NOTE: For restricting access to a rack model		
	HP Graphic Card Support Kit	660582-B21	
	NOTE: The ML350p Gen8 supports up to 3 graphic cards. HP Graphic Card Support Kit (660582-B21) will be required per Graphic Card HP 3rd Graphic Card Power Cable FIO Kit (700835-B21) will be an additional request for the 3rd graphics card support NOTE: Please see the HP Power Advisor for estimated power consumption of		
	your individual system configuration prior to installing GPUs. The HP Power Advisor is located at: www.hp.com/go/hppoweradvisor.		
	HP ML350p Gen8 Smart Array Cable Kit NOTE: While P430 purchased, this option kit needs to be purchased.	725675-B21	
HP Processors	Entry Processors - E5-2600 v2 series Processors		
	NOTE: All support up to 1333MHz memory speeds.	700004 D04	
	HP ML350p Gen8 Intel® Xeon® E5-2609v2 (2.5GHz/4-core/10MB/80W) Processor Kit	722284-B21	
	HP ML350p Gen8 Intel® Xeon® E5-2603v2 (1.8GHz/4-core/10MB/80W) Processor Kit	722285-B21	
	Base Processors - E5-2600 v2 series Processors		
	NOTE: All support up to1600MHz DDR3 memory speeds.		
	HP ML350p Gen8 Intel® Xeon® E5-2640v2 (2.0GHz/8-core/20MB/95W) Processor Kit	709491-B21	
	HP ML350p Gen8 Intel® Xeon® E5-2630v2 (2.6GHz/6-core/15MB/80W) Processor Kit	709492-B21	
	HP ML350p Gen8 Intel® Xeon® E5-2620v2 (2.1GHz/6-core/15MB/80W) Processor Kit	709493-B21	
	HP ML350p Gen8 Intel® Xeon® E5-2630Lv2 (2.4GHz/6-core/15MB/60W) Processor Kit	722287-B21	
	Performance Processors - E5-2600 v2 series Processors NOTE: All support up to 1866MHz DDR3 memory speeds.		
	HP ML350p Gen8 Intel® Xeon® E5-2697v2 (2.7GHz/12-core/30MB/130W) Processor Kit	722301-B21	
	HP ML350p Gen8 Intel® Xeon® E5-2690v2 (3.0GHz/10-core/25MB/130W) Processor Kit	709486-B21	
	HP ML350p Gen8 Intel® Xeon® E5-2680v2 (2.8GHz/10-core/25MB/115W) Processor Kit	709487-B21	
	HP ML350p Gen8 Intel® Xeon® E5-2670v2 (2.5GHz/10-core/25MB/115W) Processor Kit	709488-B21	
	HP ML350p Gen8 Intel® Xeon® E5-2667v2 (3.3GHz/8-core/25MB/130W) Processor Kit	722303-B21	
	HP ML350p Gen8 Intel® Xeon® E5-2650v2 (2.6GHz/8-core/20MB/95W) Processor Kit	709490-B21	



Core Options

HP ML350p Gen8 Intel® Xeon® E5-2643v2 (3.5GHz/6-core/25MB/130W) Processor Kit	722304-B21
HP ML350p Gen8 Intel® Xeon® E5-2637v2 (3.5GHz/4-core/15MB/130W) Processor Kit	722305-B21
Entry Processors - E5-2600 series Processors	
NOTE: All support up to 1066MHz memory speeds.	
HP ML350p Gen8 Intel® Xeon® E5-2609 (2.40GHz/4-core/10MB/80W) Processor Kit	660597-B21
HP ML350p Gen8 Intel® Xeon® E5-2603 (1.8GHz/4-core/10MB/80W) Processor Kit	660595-B21
Base Processors - E5-2600 series Processors	
NOTE: All support up to1333MHz DDR3 memory speeds.	
HP ML350p Gen8 Intel® Xeon® E5-2640 (2.5GHz/6-core/15MB/95W) Processor Kit	660600-B21
HP ML350p Gen8 Intel® Xeon® E5-2630 (2.30GHz/6-core/15MB/95W) Processor Kit	660599-B21
HP ML350p Gen8 Intel® Xeon® E5-2620 (2.0GHz/6-core/15MB/95W) Processor Kit	660598-B21
HP ML350p Gen8 Intel® Xeon® E5-2630L (2.0GHz/6-core/15MB/60W) Processor Kit	660607-B21
Performance Processors - E5-2600 series Processors	
NOTE: All support up to1600MHz DDR3 memory speeds.	
HP ML350p Gen8 Intel® Xeon® E5-2690 (2.9GHz/8-core/20MB/135W) Processor Kit	660605-B21
HP ML350p Gen8 Intel® Xeon® E5-2680 (2.7GHz/8-core/20MB/130W) Processor Kit	660604-B21
HP ML350p Gen8 Intel® Xeon® E5-2670 (2.6GHz/8-core/20MB/115W) Processor Kit	660603-B21
HP ML350p Gen8 Intel® Xeon® E5-2667 (2.9GHz/6-core/15MB/130W) Processor Kit	660608-B21
HP ML350p Gen8 Intel® Xeon® E5-2665 (2.4GHz/8-core/20MB/115W) Processor Kit	660596-B21
HP ML350p Gen8 Intel® Xeon® E5-2660 (2.2GHz/8-core/20MB/95W) Processor Kit	660602-B21
HP ML350p Gen8 Intel® Xeon® E5-2650 (2.0GHz/8-core/20MB/95W) Processor Kit	660601-B21
HP ML350p Gen8 Intel® Xeon® E5-2650L (1.8GHz/8-core/20MB/70W) Processor Kit	660606-B21
HP ML350p Gen8 Intel® Xeon® E5-2643 (3.3GHz/4-core/10MB/130W) Processor Kit	678242-B21
HP ML350p Gen8 Intel® Xeon® E5-2637 (3.0GHz/2-core/5MB/80W) Processor Kit	678244-B21
Processor Upgrade Kit	
HP ML350p Gen8 Processor Upgrade Lever Kit	749245-B21
NOTE: Customers who use ML350p Gen8 sandy bridge processors need to	02.10 521
purchase Heatsink lever upgrade kit 749245-B21 when plan to upgrade to Ivy bridge processor.	



Core Options

HP Memory

NOTE: HP memory from previous generation servers are not qualified or warranted with this HP ProLiant Server. HP SmartMemory is required to realize the memory performance improvements and enhanced functionality listed in this document for Gen8. For additional information, please see the HP SmartMemory QuickSpecs at:

http://h18000.www1.hp.com/products/quickspecs/14225 div/14225 div.html

NOTE: LRDIMM, RDIMM and UDIMMs are all distinct memory technologies and cannot be mixed within a server. The majority of ProLiant Gen8 servers support RDIMM, UDIMM and LRDIMM.

Notivity, Oblivity and Explivity.	
Registered DIMMs (RDIMMs) NOTE: The following memory is supported by the E5-2600 v2 series Processors.	
HP 4GB (1x4GB) Single Rank x4 PC3L-12800R (DDR3-1600) Registered CAS-11 Low Voltage Memory Kit	713981-B21
HP 4GB (1x4GB) Single Rank x4 PC3-14900R (DDR3-1866) Registered CAS-13 Memory Kit	708637-B21
HP 8GB (1x8GB) Dual Rank x4 PC3L-12800R (DDR3-1600) Registered CAS-11 Low Voltage Memory Kit	713983-B21
HP 8GB (1x8GB) Single Rank x4 PC3L-12800R (DDR3-1600) Registered CAS-11 Low Voltage Memory Kit	731765-B21
HP 8GB (1x8GB) Dual Rank x4 PC3-14900R (DDR3-1866) Registered CAS-13 Memory Kit	708639-B21
HP 8GB (1x8GB) Single Rank x4 PC3-14900R (DDR3-1866) Registered CAS-13 Memory Kit	731761-B21
HP 16GB (1x16GB) Dual Rank x4 PC3L-12800R (DDR3-1600) Registered CAS-11 Low Voltage Memory Kit	713985-B21
HP 16GB (1x16GB) Dual Rank x4 PC3-14900R (DDR3-1866) Registered CAS-13 Memory Kit	708641-B21
Registered DIMMs (RDIMMs)	
NOTE : The following memory is supported by the E5-2600 series Processors.	
HP 4GB (1x4GB) Single Rank x4 PC3L-10600R (DDR3-1333) Registered CAS-9 Low Voltage Memory Kit	647893-B21
HP 4GB (1x4GB) Single Rank x4 PC3-12800R (DDR3-1600) Registered CAS-11 Memory Kit	647895-B21
HP 8GB (1x8GB) Dual Rank x4 PC3L-10600R (DDR3-1333) Registered CAS-9 Low Voltage Memory Kit	647897-B21
HP 8GB (1x8GB) Single Rank x4 PC3-12800R (DDR3-1600) Registered CAS-11 Memory Kit	647899-B21
HP 8GB (1x8GB) Dual Rank x4 PC3-12800R (DDR3-1600) Registered CAS-11 Memory Kit	690802-B21
HP 16GB (1x16GB) Dual Rank x4 PC3L-10600R (DDR3-1333) Registered CAS-9 Low Voltage Memory Kit	647901-B21
HP 16GB (1x16GB) Dual Rank x4 PC3-12800R (DDR3-1600) Registered CAS-11 Memory Kit	672631-B21
Unbuffered with ECC DIMMs (UDIMMs)	
NOTE: The following memory is supported by the E5-2600 v2 series Processors.	
HP 2GB (1x2GB) Single Rank x8 PC3L-12800E (DDR3-1600) Unbuffered CAS-11 Low Voltage Memory Kit	713975-B21
HP 2GB (1x2GB) Single Rank x8 PC3-14900E (DDR3-1866) Unbuffered CAS-13	708631-B21



Memory Kit

Core Options

HP Hard Drives	NOTE: The components of a storage subsystem (e.g. the drive, the HBA/controller, firmware, and the server backplane) should operate at the same data transfer rate or the system bandwidth will be negotiated down to an acceptable level for all components.	
	HP Half-Height SATA DVD RW JackBlack Optical Drive NOTE: A total of two optical drives can be added. A second and third optical drive requires the HP 2nd Media Bay Cage Kit (Part Number 661618-B21).	624192-B21
HP Optical Drives	HP Half-Height SATA DVD ROM JackBlack Optical Drive	624189-B21
	NOTE: All DDR3 memory option kits consist of one DIMM per kit. For detailed memory configuration rules and guidelines, please use the Online DDR3 Memory Configuration Tool: www.hp.com/go/ddr3memory-configurator. NOTE: Depending on the memory configuration and processor model, 1866MHz, 1600MHz, and 1333MHz memory may operate at a lower speed. Please see the see the "Memory" section later in this document and the Online Memory Configuration Tool for details at www.hp.com/go/ddr3memory-configurator.	
	Load Reduced DIMMs (LRDIMMs) NOTE: The following memory is supported by the E5-2600 series Processors. HP 32GB (1x32GB) Quad Rank x4 PC3L-10600L (DDR3-1333) Load Reduced CAS-9 Low Voltage Memory Kit	647903-B21
	NOTE: The following memory is supported by the E5-2600 v2 series Processors. HP 32GB (1x32GB) Quad Rank x4 PC3-14900L (DDR3-1866) Load Reduced CAS-13 Memory Kit	708643-B21
	HP 8GB (1x8GB) Dual Rank x8 PC3L-10600E (DDR3-1333) Unbuffered CAS-9 Low Voltage Memory Kit Load Reduced DIMMs (LRDIMMs)	647909-B21
	HP 8GB (1x8GB) Dual Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory Kit	669324-B21
	HP 4GB (1x4GB) Dual Rank x8 PC3L-10600E (DDR3-1333) Unbuffered CAS-9 Low Voltage Memory Kit	647907-B21
	HP 4GB (1x4GB) Dual Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory Kit	669322-B21
	Memory Kit HP 2GB (1x2GB) Single Rank x8 PC3L-10600E (DDR3-1333) Unbuffered CAS-9 Low Voltage Memory Kit	647905-B21
	Unbuffered with ECC DIMMs (UDIMMs) NOTE: The following memory is supported by the E5-2600 series Processors. HP 2GB (1x2GB) Single Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11	669320-B21
	HP 8GB (1x8GB) Dual Rank x8 PC3-14900E (DDR3-1866) Unbuffered CAS-13 Memory Kit	708635-B21
	HP 8GB (1x8GB) Dual Rank x8 PC3L-12800E (DDR3-1600) Unbuffered CAS-11 Low Voltage Memory Kit	713979-B21
	HP 4GB (1x4GB) Dual Rank x8 PC3-14900E (DDR3-1866) Unbuffered CAS-13 Memory Kit	708633-B21
	HP 4GB (1x4GB) Dual Rank x8 PC3L-12800E (DDR3-1600) Unbuffered CAS-11 Low Voltage Memory Kit	713977-B21



Core Options

NOTE: Hard drives have either a one year or three year warranty; refer to the specific hard drive QuickSpecs for details.

SAS Hot Plug with SmartDrive SFF (2.5-inch) Enterprise Drives	
HP 1.2TB 6G SAS 10K rpm SFF (2.5-inch) SC Dual Port Enterprise 3yr Warranty Hard Drive	718162-B21
HP 900GB 6G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	652589-B21
HP 600GB 6G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	652583-B21
HP 450GB 6G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	652572-B21
HP 300GB 6G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	652564-B21
HP 300GB 6G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	652611-B21
HP 146GB 6G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	652605-B21
SAS Hot Plug SmartDrive SFF (2.5-inch) Midline Drives	
HP 1TB 6G SAS 7.2K rpm SFF (2.5-inch) SC Midline 1yr Warranty Hard Drive	652749-B21
HP 500GB 6G SAS 7.2K rpm SFF (2.5-inch) SC Midline 1yr Warranty Hard Drive	652745-B21
SAS Hot Plug SmartDrive LFF (3.5-inch) Enterprise Drives	
HP 600GB 6G SAS 15K rpm LFF (3.5-inch) SC Enterprise 3yr Warranty Hard Drive	652620-B21
HP 450GB 6G SAS 15K rpm LFF (3.5-inch) SC Enterprise 3yr Warranty Hard Drive	652615-B21
SAS Hot Plug SmartDrive LFF (3.5-inch) Midline Drives	
HP 4TB 6G SAS 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	695510-B21
HP 3TB 6G SAS 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	652766-B21
HP 2TB 6G SAS 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	652757-B21
HP 1TB 6G SAS 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	652753-B21
NOTE: Please see the QuickSpecs for Technical Specifications and additional information:	
http://h18000.www1.hp.com/products/quickspecs/12244_div/12244_div.html (Worldwide)	
6G SATA Hot Plug with SmartDrive SFF (2.5-inch) Midline (MDL) Drives	
HP 1TB 6G SATA 7.2K rpm SFF (2.5-inch) SC Midline 1yr Warranty Hard Drive	655710-B21
HP 500GB 6G SATA 7.2K rpm SFF (2.5-inch) SC Midline 1yr Warranty Hard Drive	655708-B21
6G SATA Hot Plug with SmartDrive LFF (3.5-inch) Midline (MDL) Drives	
HP 4TB 6G SATA 7.2k rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	693687-B21
HP 3TB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	628061-B21
HP 2TB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	658079-B21
HP 1TB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	657750-B21
HP 500GB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	658071-B21



Core Options

NOTE: SATA hard drives have a 1-year warranty. Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/13021_div/13021_div.html (Worldwide)	
12G SAS High Endurance Hot Plug SFF (2.5-inch) Enterprise Performance Solid State Drives	
HP 800GB 12G SAS High Endurance SFF 2.5-in SC Enterprise Performance 3yr Wty Solid State Drive NOTE: This drive supports Gen8 servers only.	741159-B21
HP 400GB 12G SAS High Endurance SFF 2.5-in SC Enterprise Performance 3yr Wty Solid State Drive NOTE: This drive supports Gen8 servers only.	741155-B21
HP 200GB 12G SAS High Endurance SFF 2.5-in SC Enterprise Performance 3yr Wty Solid State Drive NOTE: This drive supports Gen8 servers only.	741151-B21
12G SAS Mainstream Endurance Hot Plug SFF (2.5-inch) Enterprise	
Mainstream Solid State Drives HP 800GB 12G SAS Mainstream Endurance SFF 2.5-in SC Enterprise	741146-B21
Mainstream 3yr Wty Solid State Drive NOTE: This drive supports Gen8 servers only.	741140-021
HP 400GB 12G SAS Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive NOTE: This drive supports Gen8 servers only.	741142-B21
HP 200GB 12G SAS Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive NOTE: This drive supports Gen8 servers only.	741138-B21
6G SATA Value Endurance Hot Plug LFF (3.5-inch) Enterprise Boot Solid State Drives	
HP 120GB 6G SATA Value Endurance LFF 3.5-in SC Enterprise Boot 3yr Wty Solid State Drive	718171-B21
HP 80GB 6G SATA Value Endurance LFF 3.5-in SC Enterprise Boot 3yr Wty Solid State Drive	734362-B21
6G SATA Value Endurance Hot Plug SFF (2.5-inch) Enterprise Boot Solid State Drives	
HP 120GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Boot 3yr Wty Solid State Drive	717965-B21
HP 80GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Boot 3yr Wty Solid State Drive	734360-B21
6G SATA Value Endurance Hot Plug SFF (2.5-inch) Enterprise Value Solid State Drives	
HP 600GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty Solid State Drive	739898-B21
HP 300GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty Solid State Drive	739888-B21
HP 800GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty Solid State Drive	717973-B21
HP 480GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty Solid State Drive	717971-B21



Core Options

HP 240GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty Solid State Drive	717969-B21
6G SATA Value Endurance Hot Plug LFF (3.5-inch) Enterprise Value Solid State Drives	
HP 800GB 6G SATA Value Endurance LFF 3.5-in SC Enterprise Value 3yr Wty Solid State Drive	718189-B21
HP 600GB 6G SATA Value Endurance LFF 3.5-in SC Enterprise Value 3yr Wty Solid State Drive	739900-B21
HP 480GB 6G SATA Value Endurance LFF 3.5-in SC Enterprise Value 3yr Wty Solid State Drive	718183-B21
HP 300GB 6G SATA Value Endurance LFF 3.5-in SC Enterprise Value 3yr Wty Solid State Drive	739890-B21
HP 240GB 6G SATA Value Endurance LFF 3.5-in SC Enterprise Value 3yr Wty Solid State Drive	718177-B21
6G SATA ME Hot Plug SFF (2.5-inch) Enterprise Mainstream Solid State Drives	
HP 800GB 6G SATA Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691868-B21
HP 400GB 6G SATA Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691866-B21
HP 200GB 6G SATA Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691864-B21
HP 100GB 6G SATA Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691862-B21
6G SATA ME Hot Plug SFF (3.5-inch) Enterprise Mainstream Solid State Drives	
HP 800GB 6G SATA Mainstream Endurance LFF 3.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691860-B21
HP 400GB 6G SATA Mainstream Endurance LFF 3.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691856-B21
HP 200GB 6G SATA Mainstream Endurance LFF 3.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691854-B21
HP 100GB 6G SATA Mainstream Endurance LFF 3.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691852-B21
6G SAS ME Hot Plug SFF (2.5-inch) Enterprise Mainstream Solid State Drives	
HP 400GB 6G SAS Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	690827-B21
12G SAS VE SFF (2.5-inch) SC EV Solid State Drives	
HP 1.6TB 12G SAS Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty Solid State Drive	762263-B21
HP 800GB 12G SAS Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty Solid State Drive	762261-B21
12G SAS VE LFF (3.5-inch) SCC EV Solid State Drives	
HP 1.6TB 12G SAS Value Endurance LFF 3.5-in SC Enterprise Value 3yr Wty Solid State Drive	762272-B21
HP 800GB 12G SAS Value Endurance LFF 3.5-in SC Enterprise Value 3yr Wty Solid State Drive	762270-B21



Core Options

NOTE: Please see the QuickSpecs for Technical Specifications and additional information:

http://h18000.www1.hp.com/products/quickspecs/14038_div/14038_div.html (Worldwide)

Hard Drive Kits

NOTE: All Factory Integrated Models will be populated with sufficient hard drive blanks based on the number of initial hard drives ordered with the server.

HP 2nd Media Bay Cage Kit	661618-B21
HP 5U 6 Large Form Factor (LFF) Hot Plug Drive Cage Kit	659485-B21
HP 5U 8 Small Form Factor (SFF) Hot Plug Drive Cage Kit	659484-B21
HP 5U 6 LFF Expander Hard Drive Cage Kit	661717-B21
HP 5U 8 SFF Expander Hard Drive Cage Kit	661714-B21
HP SFF Gen8 Hard Drive Blank Kit	666987-B21
HP LFF Gen8 Hard Drive Blank Kit	666986-B21

NOTE: Mixing of SFF and LFF drive cages is not allowed.

NOTE: Additional Hot Plug Drive Cages require a separate Smart Array controller for each drive cage. HP recommends the HP Smart Array P420/1GB FBWC 6Gb 2-ports Int SAS Controller (P/N 631670-B21).

NOTE: Expander HDD Cage Kit allows up to 18 LFF / 24 SFF HDDs managed under one single controller. The controller must have a minimum of 512MB FBWC module installed.

HP Networking	Gigabit Ethernet adapters	
	HP NC112T PCI Express Gigabit Server Adapter	503746-B21
	HP NC365T 4-port Ethernet Server Adapter	593722-B21
	HP Ethernet 1Gb 4-port 331T Adapter	647594-B21
	HP Ethernet 1Gb 2-port 332T Adapter	615732-B21
	HP Ethernet 1Gb 2-port 361T Adapter	652497-B21
	10 Gigabit Ethernet adapters	
	HP NC523SFP 10Gb 2-port Server Adapter	593717-B21
	HP Ethernet 10Gb 2-port 530SFP Adapter	652503-B21
	HP Ethernet 10Gb 2-port 530T Adapter	656596-B21
	HP NC552SFP 10Gb 2-port Ethernet Server Adapter	614203-B21
	HP Ethernet 10Gb 2-port 560SFP+ Adapter	665249-B21
	HP Ethernet 10Gb 2-port 561T Adapter	716591-B21
	NOTE: Please see the QuickSpecs for Technical Specifications and additional information: www.hp.com/go/ProLiantNICs	
HP InfiniBand	QLogic InfiniBand 4X QDR PCI-E G2 Dual Port HCA	583211-B21
	HP InfiniBand FDR 2-port 545QSFP Adapter	702211-B21
	NOTE: Please see the QuickSpecs for additional information: http://h18000.www1.hp.com/products/quickspecs/13078_div/13078_div.html	



Core Options

HP Power Supplies

NOTE: Mixing of power supplies in the same server is not supported. All power supplies inside a server must be exactly the same model. Mixing Gold, Platinum, and Platinum Plus certified power supplies is not supported.

NOTE: Prior to making a power supply selection it is highly recommended that the HP Power Advisor is run to determine the right size power supply for your server configuration. The HP Power Advisor is located at: www.hp.com/go/hppoweradvisor

HP Common Slot Platinum Plus Power Supply Kits

NOTE: The following Power Supplies offer 94% Efficiency with support for Intelligent Power Discovery.

HP 460W Common Slot Platinum Plus Hot Plug Power Supply Kit	656362-B21
HP 750W Common Slot Platinum Plus Hot Plug Power Supply Kit	656363-B21
HP 1200W Common Slot Platinum Plus Hot Plug Power Supply Kit	656364-B21

HP Common Slot Gold Power Supplies

NOTE: The following Power Supplies offer up to 92% efficiency.

HP 460W Common Slot Gold Hot Plug Power Supply Kit	503296-B21
HP 750W Common Slot Gold Hot Plug Power Supply Kit	512327-B21

HP Common Slot -48VDC Power Supplies

HP 750W Common Slot -48VDC Hot Plug Power Supply Kit

NOTE: The HP 750W Common Slot -48VDC power supply does not ship with a power cable. It has been designed with a terminal block connection allowing for custom design of power cords by the user.

NOTE: Option Kits for AC power supplies include the power supply and one PDU IEC cable.

NOTE: Power Specification and Technical Content for supported power supplies can be found at:

http://h18000.www1.hp.com/products/quickspecs/14209_div/14209_div.html

HP Cooling Options

HP Hot Plug Redundant Fan Kit

659486-B21

636673-B21



Additional Options

NOTE: Some options may not be integrated at the factory. To ensure only valid configurations are ordered, HP recommends the use of an HP approved configurator. Contact your local sales representative for additional information.

HP I	nsight	Softwa	are
------	--------	--------	-----

HP Insight Control

HP Insight Control including 1yr 24x7 Technical Support and Updates Single C6N27A

Server License

HP Insight Control including 1yr 24x7 Technical Support and Updates Electronic C6N28ABE

License

NOTE: The Electronic software license is available in EMEA only.

HP Insight Control Server Provisioning Media Kit BD883A

HP Insight Management Media Kit

NOTE: Electronic and Flexible-Quantity licenses can be used to purchase multiple licenses with a single activation key.

NOTE: Customer will receive a license entitlement certificate. The license entitlement certificate must be redeemed online or via fax in order to obtain the license activation key(s). Includes one year of 24 x 7 HP Software Technical Support and Update Service.

NOTE: Licenses ship without media. The HP Insight Control Media Kit can be ordered separately, or can be downloaded at:

http://www.hp.com/go/insightupdates.

NOTE: For additional license options please see the QuickSpecs at: http://h18000.www1.hp.com/products/quickspecs/12631_div/12631_div.html

HP Integrated Lights-Out (iLO) Advanced for ProLiant

HP iLO Advanced including 1yr 24x7 Technical Support and Updates E-LTU E6U59ABE

NOTE: The Electronic software license is available in EMEA only.

HP iLO Advanced including 3yr 24x7 Technical Support and Updates E-LTU E6U64ABE

NOTE: The Electronic software license is available in EMEA only.

HP iLO Advanced including 1yr 24x7 Technical Support and Updates Single 512485-B21

Server License

HP iLO Advanced 1 Server License with 3yr 24x7 Tech Support and Updates

NOTE: For additional license options please see the QuickSpecs at: http://h18004.www1.hp.com/products/quickspecs/14276_div/14276_div.html

NOTE: For more information, visit: http://www.hp.com/go/ilo



C6N31A

BD505A

Additional Options

High	Performance
Clust	ers

HP Insight Cluster Management Utility

HP Insight Cluster Management Utility 1yr 24x7 Flexible License	QL803B
HP Insight Cluster Management Utility 3yr 24x7 Flexible License	BD476A

NOTE: These part numbers can be used to purchase one certificate for multiple licenses and support with a single activation key. Each license is for one node (server). Customer will receive a printed end user license agreement and license entitlement certificate via physical shipment. The license entitlement certificate must be redeemed online in order to obtain a license key. Customer also will receive a support agreement.

HP Insight Cluster Management Utility Media

BD477A

NOTE: For additional license kits please see the QuickSpecs at: http://h18004.www1.hp.com/products/quickspecs/12612 div/12612 div.html (Worldwide)

HP I/O Accelerator Options

Second Generation Accelerators

HP 365GB Multi Level Cell G2 PCle ioDrive2 for ProLiant Servers	673642-B21
HP 785GB Multi Level Cell G2 PCIe ioDrive2 for ProLiant Servers	673644-B21
HP 1205GB Multi Level Cell G2 PCle ioDrive2 for ProLiant Servers	673646-B21
HP 2410GB Multi Level Cell G2 PCle ioDrive2 Duo for ProLiant Servers	673648-B21
HP 3TB G2 FH/HL PCIe ioDrive2 IO Accelerator for ProLiant Servers	721458-B21
NOTE: Disease see the Quick Space for Tachnical Specifications and additional	

NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/13587 div/13587 div.html

(Worldwide)

LID 4 ATD LULIUU NA 1 C

HP PCIe Workload Accelerator Options

Mainstream Endurance (ME) PCIe Workload Accelerators

HP 1.41B HH/HL Mainstream Endurance (ME) PCIe Workload Accelerator	/29307-B21
HP 700GB HH/HL Mainstream Endurance (ME) PCIe Workload Accelerator	729305-B21

High Endurance (HE) PCIe Workload Accelerators

1:1/5 //5/50/34/11 14 1	
HP 350GB HH/HL High Endurance (HE) PCIe Workload Accelerator	708088-B21
HP 700GB HH/HL High Endurance (HE) PCIe Workload Accelerator	708090-B21

Light Endurance (LE) PCIe Workload Accelerators

HP 5.2TB FH/HL Light Endurance (LE) PCIe Workload Accelerator	775672-B21
HP 2.6TB HH/HL Light Endurance (LE) PCIe Workload Accelerator	775670-B21
HP 1.3TB HH/HL Light Endurance (LE) PCIe Workload Accelerator	775668-B21
HP 1.0TB HH/HL Light Endurance (LE) PCIe Workload Accelerator	775666-B21

NOTE: Please see the QuickSpecs for Technical Specifications and additional information:

http://h18000.www1.hp.com/products/guickspecs/14528_div/14528_div.html (Worldwide)



1

Additional Options

HP Computation and Graphics Accelerators

NOTE: Only the below listed Graphics cards are HP standard supported options in this server.

NOTE: The ML350p Gen8 supports up to 3 graphic cards. HP Graphic Card Support Kit (660582-B21) will be required per Graphic Card.

NOTE: Please see the HP Power Advisor for estimated power consumption of your individual system configuration prior to installing GPUs. The HP Power

Advisor is located at: www.hp.com/go/hppoweradvisor.

HP Graphic Card Support Kit

NVIDIA Quadro K2000 PCIe Graphics Adapter

753959-B21

NVIDIA Quadro K4000 PCI-E Graphics Adapter

730870-B21

NVIDIA Quadro K5000 PCI-E Graphics Adapter

730872-B21

NVIDIA Quadro K6000 PCI-E Graphics Adapter

730874-B21

NVIDIA Tesla K40C 12GB Computational Accelerator

753960-B21

NOTE: Min/Max rule does not apply to this option. However maximum of Three HP Graphic Card Support Kit can be selected. This Graphic Card Support Kit must be selected along with Graphic cards only.

NOTE: For all NVIDIA cards, OS support is for 64-bit versions only; Red Hat Enterprise Linux Server Editions 5.x & 6.x, SUSE Linux Enterprise Server Edition SLES11 SPx, Windows Server 2012 R2

HP Security

HP Trusted Platform Module Option

NOTE: The TPM (Trusted Platform Module) is a microcontroller chip that can securely store artifacts used to authenticate the server platform. These artifacts can include passwords, certificates and encryption keys. Windows® BitLocker™ Drive Encryption (BitLocker) is a data protection feature available in Windows Server® 2008. BitLocker leverages the enhanced security capabilities of a Trusted Platform Module (TPM) version 1.2. The TPM works with BitLocker to help protect user data and to ensure that a server running Windows Server 2008 has not been tampered with while the system was offline. For more information about TPM, including a white paper, go to: www.hp.com/go/TPM.

NOTE: ProLiant OS pre-installed units will come with the partition required for TPM deployment.

NOTE: The TPM key is unique to every TPM deployed server and must be retained. Misplacing or losing the key could result in data loss.

HP Security Bezel Kit 660584-B21

NOTE: For restricting access to a rack model

HP Secure Encryption

HP Secure Encryption No Media E-LTU per Drive

NOTE: Global except China.

HP Secure Encryption No Media Flexible License per Drive

NOTE: China Only.

NOTE: For more information about HP Secure Encryption, please visit:

http://www.hp.com/go/hpsecureencryption

HP Storage Controllers SAS Controllers

HP Smart Array P420 Controller

HP Smart Array P420/2GB FBWC 6Gb 2-ports Int SAS Controller

631671-B21

D8S85AAE

D8S84A

488069-B21



Additional Options

HP Smart Array P420/1GB FBWC 6Gb 2-ports Int SAS Controller	631670-B21
NOTE: The HP Smart Array P420 controllers are not supported in Slots 3 and 4.	
HP Smart Array P421 Controller	
HP Smart Array P421/2GB FBWC 6Gb 2-ports Ext SAS Controller	631674-B21
HP Smart Array P421/1GB FBWC 6Gb 2-ports Ext SAS Controller	631673-B21
Smart Array P430 Controller	
HP Smart Array P430/2GB FBWC 12Gb 1-port Int SAS Controller	698529-B21
HP Smart Array P430/4GB FBWC 12Gb 1-port Int SAS Controller	698530-B21
NOTE : The HP Smart Array P430 controller is not supported in Slots 3 and 4.	
Smart Array P431 Controller	
HP Smart Array P431/2GB FBWC 12Gb 2-ports Ext SAS Controller	698531-B21
HP Smart Array P431/4GB FBWC 12Gb 2-ports Ext SAS Controller	698532-B21
NOTE: The HP Smart Array P431 controller is not supported in Slot 2.	
HP Smart Array P822 Controller	
HP Smart Array P822/2GB FBWC 6Gb 2-ports-Int/4-ports Ext SAS Controller NOTE : The HP Smart Array P822 controller is not supported in Slots 1,2,5,6,7,8 or 9. The controller also is not supported in Slot 3 if Slot 4 is populated with a controller.	615418-B21
HP Smart Array P830 Controller	
HP Smart Array P830/4GB FBWC 12Gb 2-ports Int SAS Controller	698533-B21
Optional Upgrades	
HP 1GB P-series Smart Array Flash Backed Write Cache	631679-B21
HP 2GB P-series Smart Array Flash Backed Write Cache	631681-B21
HP 512MB P-series Smart Array Flash Backed Write Cache	661069-B21
HP SmartCache No Media 24x7 Technical Support 1 Svr License	D7S26A
HP SmartCache No Media 24x7 Technical Support Flexible License	D7S27A
HP SmartCache No Media 24x7 Technical Support Electronic License	D7S27AAE
NOTE: Please see the QuickSpecs for Technical Specifications and additional information:	
http://h18000.www1.hp.com/products/quickspecs/14228_div/14228_div.html (Smart Array P420 Controller)	
http://h18000.www1.hp.com/products/quickspecs/14229_div/14229_div.html (Smart Array P421 Controller)	
http://h18000.www1.hp.com/products/quickspecs/14624_div/14624_div.html (Smart Array P430 Controller)	
http://h18000.www1.hp.com/products/quickspecs/14625_div/14625_div.html	
(Smart Array P431 Controller)	
http://h18000.www1.hp.com/products/quickspecs/14341_div/14341_div.html	
(Smart Array P822 Controller) http://h18000.www1.hp.com/products/quickspecs/14744_div/14744_div.html (Smart Array P830 Controller)	
http://h18000.www1.hp.com/products/quickspecs/14532_div/14532_div.html (SmartCache)	
HP Host Bus Adapters	
HP H220 Host Bus Adapter	650933-B21
HP H221 PCIe 3.0 SAS Host Bus Adapter	729552-B21
	. 20002 021



Additional Options

see: http://www.hp.com/go/tape. For hardware and software compatibility of HP tape backup products see: http://www.hp.com/storage/SPOCK and www.hp.com/go/ebs. NOTE: Installation of tape drive requires ordering of 2nd Media Bay Cage, Part Number 661618-B21. HP StoreEver LTO-6 Ultrium 6250 Tape Drive in 1U Rack-mount Kit C0L99A HP StoreEver LTO-6 Ultrium 6650 SAS Internal Tape Drive EH963A HP StoreEver LTO-6 Ultrium 6050 SAS External Tape Drive EH964A HP StoreEver LTO-6 Ultrium 6250 Internal Tape Drive EH969A HP StoreEver LTO-6 Ultrium 6250 External Tape Drive EH970A HP StoreEver 1/8 G2 LTO-6 Ultrium 6250 FC Tape Autoloader C0H19A	Additional Options		
information: http://h18004.www1.hp.com/products/quickspecs/14336_div/14336_div.html (HBA 220) http://h18004.www1.hp.com/products/quickspecs/14222_div/14222_div.html (HBA 221) http://h18004.www1.hp.com/products/quickspecs/14337_div/14337_div.html (HBA 221) http://h18004.www1.hp.com/products/quickspecs/14337_div/14337_div.html (HBA 222) SCSI HBA HP SC11Xe Ultra320 Single Channel/ PCle x4 SCSI Host Bus Adapter 412911-B21 NOTE: Supports external drive attach NOTE: Please see the following QuickSpecs for additional information: http://h18000.www1.hp.com/products/quickspecs/12566_div/12566_div.html HP Tape Backup NOTE: For the complete range of tape drives, autoloaders, libraries and media see: http://www.hp.com/go/ebs. NOTE: Installation of tape drive requires ordering of 2nd Media Bay Cage, Part Number 661618-B21. HP StoreEver LTO-6 Ultrium 6250 Tape Drive in 1U Rack-mount Kit C0L99A HP StoreEver LTO-6 Ultrium 6650 SAS Internal Tape Drive EH963A HP StoreEver LTO-6 Ultrium 6250 Internal Tape Drive EH964A HP StoreEver LTO-6 Ultrium 6250 Internal Tape Drive EH969A HP StoreEver LTO-6 Ultrium 6250 External Tape Drive EH969A HP StoreEver LTO-6 Ultrium 6250 FC Tape Autoloader C0H19A HP Tape Storage Systems HP StoreEver MSL6480 HP StoreEver MSL6480 HP StoreEver MSL6480 Scalable Base Module NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/14604_div/14604_div.html		HP H222 Host Bus Adapter	650926-B21
(HBA 221) http://h18004.www1.hp.com/products/quickspecs/14337_div/14337_div.html (HBA 222) SCSI HBA HP SC11Xe Ultra320 Single Channel/ PCIe x4 SCSI Host Bus Adapter NOTE: Supports external drive attach NOTE: Please see the following QuickSpecs for additional information: http://h18000.www1.hp.com/products/quickspecs/12566_div/12566_div.html HP Tape Backup NOTE: For the complete range of tape drives, autoloaders, libraries and media see: http://www.hp.com/go/ebs. NOTE: Installation of tape drive requires ordering of 2nd Media Bay Cage, Part Number 661618-B21. HP StoreEver LTO-6 Ultrium 6250 Tape Drive in 1U Rack-mount Kit COL99A HP StoreEver LTO-6 Ultrium 6650 SAS External Tape Drive EH963A HP StoreEver LTO-6 Ultrium 6650 SAS External Tape Drive EH964A HP StoreEver LTO-6 Ultrium 6250 Internal Tape Drive EH964A HP StoreEver LTO-6 Ultrium 6250 External Tape Drive EH970A HP StoreEver LTO-6 Ultrium 6250 External Tape Drive EH970A HP StoreEver MSL6480 HP StoreEver MSL6480 Scalable Base Module NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/14604_div/14604_div.html		information: http://h18004.www1.hp.com/products/quickspecs/14336_div/14336_div.html	
(HBA 222) SCSI HBA HP SC11Xe Ultra320 Single Channel/ PCle x4 SCSI Host Bus Adapter NOTE: Supports external drive attach NOTE: Please see the following QuickSpecs for additional information: http://h18000.www1.hp.com/products/quickspecs/12566_div/12566_div.html HP Tape Backup NOTE: For the complete range of tape drives, autoloaders, libraries and media see: http://www.hp.com/go/tape. For hardware and software compatibility of HP tape backup products see: http://www.hp.com/storage/SPOCK and www.hp.com/go/tape. NOTE: Installation of tape drive requires ordering of 2nd Media Bay Cage, Part Number 661618-B21. HP StoreEver LTO-6 Ultrium 6250 Tape Drive in 1U Rack-mount Kit C0L99A HP StoreEver LTO-6 Ultrium 6650 SAS Internal Tape Drive EH963A HP StoreEver LTO-6 Ultrium 6650 SAS External Tape Drive EH964A HP StoreEver LTO-6 Ultrium 6250 Internal Tape Drive EH969A HP StoreEver LTO-6 Ultrium 6250 External Tape Drive EH970A HP StoreEver LTO-6 Ultrium 6250 FC Tape Autoloader HP StoreEver 1/8 G2 LTO-6 Ultrium 6250 FC Tape Autoloader QU625A NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/14604_div/14604_div.html		(HBA 221)	
HP SC11Xe Ultra320 Single Channel/ PCle x4 SCSI Host Bus Adapter NOTE: Supports external drive attach NOTE: Please see the following QuickSpecs for additional information: http://h18000.www1.hp.com/products/quickspecs/12566_div/12566_div.html NOTE: For the complete range of tape drives, autoloaders, libraries and media see: http://www.hp.com/go/tape. For hardware and software compatibility of HP tape backup products see: http://www.hp.com/storage/SPOCK and www.hp.com/go/ebs. NOTE: Installation of tape drive requires ordering of 2nd Media Bay Cage, Part Number 661618-B21. HP StoreEver LTO-6 Ultrium 6250 Tape Drive in 1U Rack-mount Kit C0L99A HP StoreEver LTO-6 Ultrium 6650 SAS Internal Tape Drive EH963A HP StoreEver LTO-6 Ultrium 6650 SAS External Tape Drive EH964A HP StoreEver LTO-6 Ultrium 6250 Internal Tape Drive EH969A HP StoreEver LTO-6 Ultrium 6250 External Tape Drive EH969A HP StoreEver LTO-6 Ultrium 6250 External Tape Drive EH970A HP StoreEver MSL6480 HP StoreEver MSL6480 HP StoreEver MSL6480 Scalable Base Module NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/14604_div/14604_div.html			
NOTE: Supports external drive attach NOTE: Please see the following QuickSpecs for additional information: http://h18000.www1.hp.com/products/quickspecs/12566_div/12566_div.html NOTE: For the complete range of tape drives, autoloaders, libraries and media see: http://www.hp.com/go/tape. For hardware and software compatibility of HP tape backup products see: http://www.hp.com/storage/SPOCK and www.hp.com/go/ebs. NOTE: Installation of tape drive requires ordering of 2nd Media Bay Cage, Part Number 661618-B21. HP StoreEver LTO-6 Ultrium 6250 Tape Drive in 1U Rack-mount Kit C0L99A HP StoreEver LTO-6 Ultrium 6650 SAS Internal Tape Drive EH963A HP StoreEver LTO-6 Ultrium 6650 SAS External Tape Drive EH964A HP StoreEver LTO-6 Ultrium 6250 Internal Tape Drive EH969A HP StoreEver LTO-6 Ultrium 6250 External Tape Drive EH969A HP StoreEver LTO-6 Ultrium 6250 External Tape Drive EH970A HP StoreEver MSL6480 HP StoreEver MSL6480 HP StoreEver MSL6480 HP StoreEver MSL6480 Scalable Base Module NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/14604_div/14604_div.html		SCSI HBA	
NOTE: Please see the following QuickSpecs for additional information: http://h18000.www1.hp.com/products/quickspecs/12566_div/12566_div.html NOTE: For the complete range of tape drives, autoloaders, libraries and media see: http://www.hp.com/go/tape. For hardware and software compatibility of HP tape backup products see: http://www.hp.com/storage/SPOCK and www.hp.com/go/ebs. NOTE: Installation of tape drive requires ordering of 2nd Media Bay Cage, Part Number 661618-B21. HP StoreEver LTO-6 Ultrium 6250 Tape Drive in 1U Rack-mount Kit C0L99A HP StoreEver LTO-6 Ultrium 6650 SAS Internal Tape Drive EH963A HP StoreEver LTO-6 Ultrium 6650 SAS External Tape Drive EH964A HP StoreEver LTO-6 Ultrium 6250 Internal Tape Drive EH969A HP StoreEver LTO-6 Ultrium 6250 External Tape Drive EH970A HP StoreEver LTO-6 Ultrium 6250 External Tape Drive EH970A HP StoreEver 1/8 G2 LTO-6 Ultrium 6250 FC Tape Autoloader C0H19A HP Tape Storage Systems HP StoreEver MSL6480 Systems HP StoreEver MSL6480 Scalable Base Module QU625A NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/14604_div/14604_div.html		HP SC11Xe Ultra320 Single Channel/ PCIe x4 SCSI Host Bus Adapter	412911-B21
http://h18000.www1.hp.com/products/quickspecs/12566_div/12566_div.html NOTE: For the complete range of tape drives, autoloaders, libraries and media see: http://www.hp.com/go/tape. For hardware and software compatibility of HP tape backup products see: http://www.hp.com/storage/SPOCK and www.hp.com/go/ebs. NOTE: Installation of tape drive requires ordering of 2nd Media Bay Cage, Part Number 661618-B21. HP StoreEver LTO-6 Ultrium 6250 Tape Drive in 1U Rack-mount Kit COL99A HP StoreEver LTO-6 Ultrium 6650 SAS Internal Tape Drive EH963A HP StoreEver LTO-6 Ultrium 6650 SAS External Tape Drive EH964A HP StoreEver LTO-6 Ultrium 6250 Internal Tape Drive EH969A HP StoreEver LTO-6 Ultrium 6250 External Tape Drive EH970A HP StoreEver LTO-6 Ultrium 6250 External Tape Drive COH19A HP Tape Storage Systems HP StoreEver MSL6480 HP StoreEver MSL6480 Scalable Base Module QU625A NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/14604_div/14604_div/html		NOTE: Supports external drive attach	
see: http://www.hp.com/go/tape. For hardware and software compatibility of HP tape backup products see: http://www.hp.com/storage/SPOCK and www.hp.com/go/ebs. NOTE: Installation of tape drive requires ordering of 2nd Media Bay Cage, Part Number 661618-B21. HP StoreEver LTO-6 Ultrium 6250 Tape Drive in 1U Rack-mount Kit C0L99A HP StoreEver LTO-6 Ultrium 6650 SAS Internal Tape Drive EH963A HP StoreEver LTO-6 Ultrium 6650 SAS External Tape Drive EH964A HP StoreEver LTO-6 Ultrium 6250 Internal Tape Drive EH969A HP StoreEver LTO-6 Ultrium 6250 External Tape Drive EH970A HP StoreEver LTO-6 Ultrium 6250 External Tape Drive EH970A HP StoreEver 1/8 G2 LTO-6 Ultrium 6250 FC Tape Autoloader C0H19A HP Tape Storage Systems HP StoreEver MSL6480 NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/14604_div/14604_div/html			
HP StoreEver LTO-6 Ultrium 6650 SAS Internal Tape Drive EH963A HP StoreEver LTO-6 Ultrium 6650 SAS External Tape Drive EH964A HP StoreEver LTO-6 Ultrium 6250 Internal Tape Drive EH969A HP StoreEver LTO-6 Ultrium 6250 External Tape Drive EH970A HP StoreEver 1/8 G2 LTO-6 Ultrium 6250 FC Tape Autoloader C0H19A HP Tape Storage Systems HP StoreEver MSL6480 HP StoreEver MSL6480 Scalable Base Module NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/14604_div/14604_div.html	HP Tape Backup	see: http://www.hp.com/go/tape. For hardware and software compatibility of HP tape backup products see: http://www.hp.com/storage/SPOCK and www.hp.com/go/ebs. NOTE: Installation of tape drive requires ordering of 2nd Media Bay Cage, Part	
HP StoreEver LTO-6 Ultrium 6650 SAS External Tape Drive HP StoreEver LTO-6 Ultrium 6250 Internal Tape Drive HP StoreEver LTO-6 Ultrium 6250 External Tape Drive HP StoreEver 1/8 G2 LTO-6 Ultrium 6250 FC Tape Autoloader HP StoreEver 1/8 G2 LTO-6 Ultrium 6250 FC Tape Autoloader C0H19A HP StoreEver MSL6480 HP StoreEver MSL6480 Scalable Base Module NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/14604_div/14604_div.html		HP StoreEver LTO-6 Ultrium 6250 Tape Drive in 1U Rack-mount Kit	C0L99A
HP StoreEver LTO-6 Ultrium 6250 Internal Tape Drive HP StoreEver LTO-6 Ultrium 6250 External Tape Drive HP StoreEver 1/8 G2 LTO-6 Ultrium 6250 FC Tape Autoloader HP StoreEver MSL6480 Systems HP StoreEver MSL6480 Scalable Base Module NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/14604_div/14604_div.html		HP StoreEver LTO-6 Ultrium 6650 SAS Internal Tape Drive	EH963A
HP StoreEver LTO-6 Ultrium 6250 External Tape Drive HP StoreEver 1/8 G2 LTO-6 Ultrium 6250 FC Tape Autoloader C0H19A HP Tape Storage Systems HP StoreEver MSL6480 HP StoreEver MSL6480 Scalable Base Module NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/14604_div/14604_div.html		HP StoreEver LTO-6 Ultrium 6650 SAS External Tape Drive	EH964A
HP StoreEver 1/8 G2 LTO-6 Ultrium 6250 FC Tape Autoloader C0H19A HP Tape Storage Systems HP StoreEver MSL6480 HP StoreEver MSL6480 Scalable Base Module NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/14604_div/14604_div.html		HP StoreEver LTO-6 Ultrium 6250 Internal Tape Drive	EH969A
HP Tape Storage Systems HP StoreEver MSL6480 HP StoreEver MSL6480 Scalable Base Module QU625A NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/14604_div/14604_div.html		HP StoreEver LTO-6 Ultrium 6250 External Tape Drive	EH970A
Systems HP StoreEver MSL6480 Scalable Base Module NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/14604_div/14604_div.html		HP StoreEver 1/8 G2 LTO-6 Ultrium 6250 FC Tape Autoloader	C0H19A
NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/14604_div/14604_div.html	HP Tape Storage	HP StoreEver MSL6480	
information: http://h18000.www1.hp.com/products/quickspecs/14604_div/14604_div.html	Systems	HP StoreEver MSL6480 Scalable Base Module	QU625A
		information:	



Additional Options

HP C)isk	Bac	kup
------	------	-----	-----

NOTE: For the complete range of RDX drives and media see:

http://www.hp.com/go/rdx. For hardware and software compatibility of HP disk

backup products see: http://www.hp.com/storage/SPOCK.

HP StoreOnce Backup systems

HP StoreOnce 4220 Backup BB855A

HP RDX Removable Disk Backup Systems USB

HP RDX320 USB3.0 External Disk Backup System

HP RDX500 USB3.0 Internal Disk Backup System

B7B64A

HP RDX500 USB3.0 External Disk Backup System

B7B66A

HP RDX500 USB3.0 External Disk Backup System
HP RDX1000 USB3.0 Internal Disk Backup System
HP RDX1000 USB3.0 External Disk Backup System

NOTE: Please see the following QuickSpecs for additional models and

information:

http://h18000.www1.hp.com/products/quickspecs/13036 div/13036 div.html

HP Disk Storage Systems

Disk Enclosures

HP D3600 Enclosure

NOTE: See the D3000 Disk Enclosure QuickSpecs for additional information including configuration steps and additional options needed for a complete solution at:

http://h18000.www1.hp.com/products/quickspecs/14866_div/14866_div.html (Worldwide)

HP D3700 Enclosure

QW967A

B7B67A B7B69A

QW968A

NOTE: See the D3000 Disk Enclosure QuickSpecs for additional information including configuration steps and additional options needed for a complete solution at:

http://h18000.www1.hp.com/products/quickspecs/14866_div/14866_div.html (Worldwide)

HP D2600 Disk Enclosure

AJ940A

NOTE: See the D2000 Disk Enclosure QuickSpecs for additional information including configuration steps and additional options needed for a complete solution at:

http://h18000.www1.hp.com/products/quickspecs/13404_div/13404_div.html (Worldwide)

HP D2700 Disk Enclosure

AJ941A

NOTE: See the D2000 Disk Enclosure QuickSpecs for additional information including configuration steps and additional options needed for a complete solution at:

http://h18000.www1.hp.com/products/quickspecs/13404_div/13404_div.html (Worldwide)

HP D6000 Dual I/O Module Disk Enclosure

QQ695A

NOTE: See the D6000 Disk Enclosure QuickSpecs for additional information including configuration steps and additional options needed for a complete solution at:

http://h18000.www1.hp.com/products/quickspecs/14419_div/14419_div.html (Worldwide)



Additional Options

HP Storage Options

NOTE: The following is a list of all Fibre Channel Host Bus Adapters for Windows and Linux. For detailed compatibility information please see: http://h18006.www1.hp.com/storage/saninfrastructure/hba.html

Brocade Fibre Channel HBAs

NOTE: HP ProLiant ML350p Gen8 Server series limited support for Red Hat Enterprise Linux 5.7 (x86and x86_64) when installing with Brocade HBAs.

Enterprise Linux 6.7 (xooding xoo_64) when installing with broader rib/to.	
HP 81B 8Gb 1-port PCle Fibre Channel Host Bus Adapter	AP769B
HP 82B 8Gb 2-port PCle Fibre Channel Host Bus Adapter	AP770B
Emulex Fibre Channel HBAs	
HP 81E 8Gb 1-port PCle Fibre Channel Host Bus Adapter	AJ762B
HP 82E 8Gb 2-port PCle Fibre Channel Host Bus Adapter	AJ763B
HP StoreFabric SN1100E 16Gb Single Port Fibre Channel Host Bus Adapter	C8R38A
HP StoreFabric SN1100E 16Gb Dual Port Fibre Channel Host Bus Adapter	C8R39A
QLogic Fibre Channel HBAs	
HP 81Q 8Gb 1-port PCle Fibre Channel Host Bus Adapter	AK344A
HP 82Q 8Gb 2-port PCle Fibre Channel Host Bus Adapter	AJ764A
HP StoreFabric SN1000Q 16GB 1-port PCle Fibre Channel Host Bus Adapter	QW971A
HP StoreFabric SN1000Q 16GB 2-port PCle Fibre Channel Host Bus Adapter	QW972A
Converged Network Adapter	
HP CN1000Q Dual Port Converged Network Adapter	BS668A
HP CN1100E Dual Port Converged Network Adapter	BK835A
HP StoreFabric CN1100R Dual Port Converged Network Adapter	QW990A

HP Uninterruptible Power Systems

HP Tower UPS

HP T750 G2 UPS Models

HP T750J JP Uninterruptible Power System

AF456A

HP T1000 G3 UPS Models

HP T1000 G3 1000VA INTL Tower Uninterruptible Power System

AF449A

HP T1000 JP Uninterruptible Power System

AF448A

HP T1000J JP Uninterruptible Power System

AF457A

HP T1500 G3 UPS Models

HP T1500 G3 1400VA INTL Tower Uninterruptible Power System

HP T1500 G3 1400VA NA Tower Uninterruptible Power System

AF450A

HP T1500J JP Uninterruptible Power System

AF458A

NOTE: Please see the QuickSpecs for additional information: http://h18000.www1.hp.com/products/quickspecs/13160_div/13160_div.html (Worldwide)

HP Rack-mountable UPS

HP R1500 G3 Uninterruptible Power Supply (UPS)

HP R1.5kVA G3 1U INTL Uninterruptible Power System	AF471A
HP R1.5kVA G3 1U JP/TW Uninterruptible Power System	AF470A
HP R1.5kVA G3 1U NA Uninterruptible Power System	AF469A



Additional Options

NOTE: Please see the QuickSpecs for additional information:

http://h18000.www1.hp.com/products/quickspecs/14059_div/14059_div.html (Worldwide)

HP R/T3000 G2 Uninterruptible Power System (UPS)

HP R/T3000 G2 2U Detachable Cord High Voltage INTL Uninterruptible Power AF468A System

HP R/T3000 G2 2U L530 Low Voltage NA/JP Uninterruptible Power System

AF466A

HP R/T3000 G2 2U L620 High Voltage NA/JP Uninterruptible Power System

AF467A

NOTE: Please see the QuickSpecs for additional information: http://h18000.www1.hp.com/products/quickspecs/14058_div/14058_div.html (Worldwide)

R5000 Uninterruptible Power System (UPS)

HP R5KVA 3U IEC309-32A High Voltage INTL Uninterruptible Power System AF461A HP R5KVA 3U L630 High Voltage NA/JP Uninterruptible Power System AF460A

NOTE: Please see the QuickSpecs for additional information: http://h18000.www1.hp.com/products/quickspecs/14109_div/14109_div.html (Worldwide)

R7000 Uninterruptible Power System (UPS)

HP R7KVA 4U 50A High Voltage NA/JP Uninterruptible Power System

AF462A

HP R7KVA 4U IEC-32A High Voltage INTL Uninterruptible Power System

AF463A

NOTE: Please see the QuickSpecs for additional information: http://h18000.www1.hp.com/products/quickspecs/14110_div/14110_div.html (Worldwide)

NOTE: For additional information on sizing your HP UPS, please reference: http://www.upssizer.com

NOTE: Please see the UPS and PDU cable matrix's on the HP Power Protection and Management page. Under Power Cords, click on the "HP Power Cord Matrix" link. That link will list cable descriptions, requirements, and specifications for UPS and PDU units. Please see the following link: www.hp.com/products/powercords. **NOTE:** For additional information on HP Uninterruptible Power Systems please go to: www.hp.com/servers/rackups.



Additional Options

HP Basic Power Distribution Units (bPDU)

HP Basic Power Distribution Unit: 1U/0U Version	
HP 1.9kVA 120 Volt L5-20 Input (12xNEMA 5-20R) NA/JP Basic PDU	H5M54A
HP 3.6kVA 200-240 Volt Detachable C20 Input (12xC13) WW Basic PDU	H5M56A
HP Basic Power Distribution Unit: Half Height Version	
HP 2.8kVA 120 Volt L5-30 Input (18xNEMA 5-20R) NA/JP Basic PDU	H5M55A
HP 3.6kVA 200-240 Volt Detachable C20 Input (18xC13) WW Basic PDU	H5M57A
HP 4.9kVA 208 Volt L6-30 Input (20xC13) NA/JP Basic PDU	H5M58A
HP 7.3kVA 230 Volt IEC309 32A Input (20xC13) INTL Basic PDU	H5M68A
HP 8.6kVA 208 Volt L15-30 3-Phase Input (18xC13) NA/JP Basic PDU	H5M61A
HP Basic Power Distribution Unit: Mid Height Version	
HP 4.9kVA 208 Volt L6-30 Input (24xC13/6xC19) NA/JP Basic PDU	H5M59A
HP 7.3kVA 230 Volt IEC309 32A Input (24xC13/6xC19) INTL Basic PDU	H5M70A
HP 8.3kVA 208 Volt CS8265C Input (30xC13/6xC19) NA/JP Basic PDU	H5M60A
HP 11kVA 230 Volt IEC309 63A Input (30xC13/6xC19) INTL Basic PDU	H5M71A
HP Hardwired 200-240 Volt Input (30xC13/6xC19) WW Basic PDU	H5M75A
HP 5.7kVA 208 Volt L21-20 3-Phase Input (24xC13/3xNEMA 5-20R) NA/JP Basic PDU	H5M63A
HP 8.6kVA 208 Volt L21-30 3-Phase Input (24xC13/3xC19/3xNEMA 5-20R) NA/JP Basic PDU	H5M64A
HP 8.6kVA 208 Volt L15-30 3-Phase Input (24xC13/6xC19) NA/JP Basic PDU	H5M62A
HP 11kVA 400 Volt IEC309 16A 3-Phase Input (30xC13/6xC19) INTL Basic PDU	H5M72A
HP Basic Power Distribution Unit: Full Height Version	
HP 11kVA 400 Volt IEC309 16A 3-Phase Input (36xC13/6xC19) INTL Basic PDU	H5M73A
HP 11kVA 400 Volt IEC309 30A 3-Phase Input (36xC13/6xC19) NA Basic PDU	H5M67A
HP Basic Power Distribution Unit: 480/277 Volt Version	
HP 13.2kVA 480 Volt IEC309 30A 3-Phase Input (15 Outlet) NA Basic PDU	H3X07A
HP 19.9kVA 480 Volt IEC309 30A 3-Phase Input (30 Outlet) NA Basic PDU	H3X08A
HP 800VA - 277V Input / 230V Output NA Rack Mount Transformer	H3X09A
NOTE: Please see the QuickSpecs for Technical Specifications and additional information:	
http://h18000.www1.hp.com/products/quickspecs/14557_div/14557_div.html (Worldwide)	
NOTE: Additional HP Power Distribution Units are available. For a complete list of all HP PDUs and additional information please visit www.hp.com/go/rackandpower.	

Power Distribution Units (mPDU)

HP Remote Monitoring HP Remote Monitored Power Distribution Unit: 1U Version HP 2.8kVA 120 Volt L5-30 Input (12xNEMA 5-20R)NA/JP Monitored PDU **D9N43A** HP 3.6kVA 200-240 Volt Detachable C20 Input (12xC13) WW Monitored PDU **D9N46A** HP 4.9kVA 208 Volt L6-30 Input (12xC13) NA/JP Monitored PDU D9N44A **HP Remote Monitored Power Distribution Unit: Half Height Version** HP 3.6kVA 200-240 Volt Detachable C20 Input (16xC13) WW Monitored PDU D9N45A **HP Remote Monitored Power Distribution Unit: Mid Height Version** HP 4.9kVA 208 Volt L6-30 Input (20xC13/4xC19) NA/JP Monitored PDU D9N47A



Additional Options

HP 7.3kVA 230 Volt IEC309 32A Input (20xC13/4xC19) INTL Monitored PDU	D9N48A
HP 8.6kVA 208 Volt L15-30 3-Phase Input (18xC13/3xC19) NA/JP Monitored PDU	D9N51A
HP 5.7kVA 208 Volt L21-20 3-Phase Input (18xC13/3xNEMA 5-20R) NA/JP	D9N52A
Monitored PDU	
HP 8.6kVA 208 Volt L21-30 3-Phase Input (20xC13/3xC19/3xNEMA 5-20R)	D9N53A
NA/JP Monitored PDU	
HP 11kVA 400 Volt IEC309 16A 3-Phase Input (18xC13/3xC19) INTL Monitored	D9N55A
PDU	
HP Remote Monitored Power Distribution Unit: Full Height Version	
HP 8.3kVA 208 Volt CS8265C Input (30xC13/3xC19) NA Monitored PDU	D9N49A
HP 7.3kVA 230 Volt IEC309 32A Input (32xC13/4xC19) INTL Monitored PDU	D9N50A
HP 11kVA 400 Volt IEC309 16A 3-Phase Input (30xC13/3xC19) INTL Monitored	D9N57A
PDU	
HP 14.4kVA 208 Volt CS8365C 3-Phase Input (12xC13/12xC19)NA Monitored	D9N58A
PDU	
HP 16.6kVA 400 Volt IEC309 30A 3-Phase Input (30xC13/3xC19) NA Monitored	D9N61A
PDU	
HP 16.6kVA 400 Volt IEC309 30A 3-Phase Input (12xC13/12xC19) NA Monitored	D9N62A
PDU	
HP 17.3kVA 208 Volt IEC309 60A 3-Phase Input (24xC13/3xC19) NA/JP	D9N54A
Monitored PDU	
HP 17.3kVA 208 Volt IEC309 60A 3-Phase Input (12xC13/12xC19) NA/JP	D9N59A
Monitored PDU	
HP 17.3kVA 208 Volt IEC309 60A 3-Phase Watertight Input (12xC13/12xC19)	G9Z07A
NA/JP Monitored PDU	D011004
HP 19.9kVA 480 Volt 3-Phase (30 Outlet) NA Monitored PDU	D9N63A
HP 22kVA 400 Volt IEC309 32A 3-Phase Input (30xC13/3xC19) INTL Monitored	D9N56A
PDU	
HP 22kVA 400 Volt IEC309 32A 3-Phase Input (12xC13/12xC19) INTL Monitored PDU	D9N60A
	007004
HP 22kVA 400 Volt IEC309 32A 3-Phase Watertight Input (12xC13/12xC19) INTL Monitored PDU	G9Z08A
HP Environmental Sensor for Remote Monitored PDUs	E0DE04
HP Environmental Sensor for Remote Monitored PDUs	E2D53A
NOTE: Please see the QuickSpecs for additional information:	
http://h18000.www1.hp.com/products/quickspecs/14669_div/14669_div.html (Worldwide)	
(Worldwide)	



Additional Options

HP Intelligent Power Distribution Units (iPDU)

iPDU Core Units	
HP 4.9kVA 24A Single Phase NA/JP Core Intelligent Modular Power Distribution	AF520A
Unit	711 02071
HP 8.3kVA 40A Single Phase NA/JP Core Intelligent Modular Power Distribution Unit	AF521A
HP 8.6kVA 24A Three Phase NA/JP Core Intelligent Modular Power Distribution Unit	AF522A
HP 14.4kVA 40A Three Phase NA/JP Intelligent Modular Power Distribution Unit	AF533A
HP 17.3kVA 48A Three Phase NA/JP Core Intelligent Modular Power Distribution Unit	AF523A
HP 17.3kVA 24A 415V Three Phase L22-30 NA Core Intelligent Power Distribution Unit	AF902A
HP 7.3kVA 32A Single Phase INTL Core Intelligent Modular Power Distribution Unit	AF525A
HP 11kVA 16A Three Phase INTL Core Intelligent Modular Power Distribution Unit	AF526A
HP 22kVA 32A Three Phase INTL Core Intelligent Modular Power Distribution Unit	AF527A
HP 17.3kVA 48A 208V Three Phase 12 Outlet Core NA/JP Intelligent Power Distribution Unit	AF535A
HP 17.3kVA 24A 415V Three Phase 12 Outlet Core NA/JP Intelligent Power Distribution Unit	AF537A
HP 22kVA 32A 400V Three Phase 12 Outlet Core INTL Intelligent Power Distribution Unit	AF538A
iPDU Kits with Standard Extension Bars	
HP 4.9kVA 24A Single Phase NA/JP Intelligent Modular Power Distribution Kit	AF531A
HP 8.6kVA 24A Three Phase NA/JP Intelligent Modular Power Distribution Kit	AF532A
HP 7.3kVA 32A Single Phase INTL Intelligent Modular Power Distribution Kit	AF534A
iPDU Extension Bars	
HP 5xC13 Intelligent PDU Extension Bar G2 Kit	AF547A
HP 5xC13 Outlets Power and UID LEDs Pair Standard Extension Bar	AF528A
NOTE: Please see the QuickSpecs for Technical Specifications and additional information:	
http://h18000.www1.hp.com/products/quickspecs/13650_div/13650_div.html (Worldwide)	
NOTE: Additional HP Power Distribution Units are available. For a complete list of all HP PDUs and additional information please visit: www.hp.com/go/rackandpower.	



Additional Options

HP Rack Series	HP Intelligent Series Rack
	HP 636 1075mm Pallet Intelligent Series Rack

HP 636 1075mm Pallet Intelligent Series Rack
HP 636 1075mm Shock Intelligent Series Rack
HP 642 1075mm Pallet Intelligent Series Rack
HP 642 1075mm Shock Intelligent Series Rack
HP 647 1075mm Pallet Intelligent Series Rack
HP 647 1075mm Pallet Intelligent Series Rack
HP 647 1075mm Shock Intelligent Series Rack
BW911A
HP 647 1075mm Shock Intelligent Series Rack
BW912A

NOTE: Please see the QuickSpecs for Technical Specifications such as height, width, depth, weight, and color:

http://h18000.www1.hp.com/products/quickspecs/14223_div/14223_div.html (Worldwide)

/vondwide)

NOTE: For additional information regarding Rack Cabinets, please see the

following URL: http://www.hp.com/go/rackandpower.

HP Rack Options HP

HP Location Discovery Services

HP 36U Location Discovery Kit	BW945A
HP 42U Location Discovery Kit	BW946A
HP 47U Location Discovery Kit	BW947A

NOTE: Please see the QuickSpecs for Technical Specifications and additional information:

http://h18000.www1.hp.com/products/quickspecs/14429_div/14429_div.html (Worldwide)

HP USB Keyboard and Mouse

HP USB BFR with PVC Free US Keyboard/Mouse Kit	631341-B21
HP USB BFR with PVC Free UK Keyboard/Mouse Kit	631344-B21
HP USB BFR with PVC Free FR Keyboard/Mouse Kit	631346-B21
HP USB BFR with PVC Free ES Keyboard/Mouse Kit	631348-B21
HP USB BFR with PVC Free DE Keyboard/Mouse Kit	631358-B21
HP USB BFR with PVC Free JP Keyboard/Mouse Kit	631360-B21
HP USB BFR with PVC Free IT Keyboard/Mouse Kit	631362-B21
HP USB BFR with PVC Free CN Keyboard/Mouse Kit	631364-B21
HP USB BFR with PVC Free AE Keyboard/Mouse Kit	638212-B21
HP USB BFR with PVC Free RU Keyboard/Mouse Kit	638214-B21
HP USB BFR with PVC Free AP-Intl Keyboard/Mouse Kit	672097-373
HP USB BFR with PVC Free Intl Keyboard/Mouse Kit	672097-B33
HP USB BFR with PVC Free PT Keyboard/Mouse Kit	672097-133
HP USB BFR with PVC Free TR Keyboard/Mouse Kit	672097-143
HP USB BFR with PVC Free CZ Keyboard/Mouse Kit	672097-223
HP USB BFR with PVC Free FI Keyboard/Mouse Kit	672097-353
HP USB BFR with PVC Free SE Keyboard/Mouse Kit	672097-103
HP USB BFR with PVC Free CH Keyboard/Mouse Kit	672097-113
HP USB BFR with PVC Free KR Keyboard/Mouse Kit	672097-KD3
HP USB BFR with PVC Free IN Keyboard/Mouse Kit	672097-D63



Additional Options

NOTE: Please see the QuickSpecs for Technical Specifications and additional http://h18000.www1.hp.com/products/quickspecs/13792 div/13792 div.html (Worldwide) HP TFT7600 G2 KVM Console Rackmount Keyboard Monitor HP TFT7600 G2 KVM Console Rackmount Keyboard US Monitor AZ870A AZ871A HP TFT7600 G2 KVM Console Rackmount Keyboard UK Monitor HP TFT7600 G2 KVM Console Rackmount Keyboard DE Monitor AZ872A HP TFT7600 G2 KVM Console Rackmount Keyboard FR Monitor AZ873A HP TFT7600 G2 KVM Console Rackmount Keyboard IT Monitor AZ874A HP TFT7600 G2 KVM Console Rackmount Keyboard ES Monitor AZ875A AZ876A HP TFT7600 G2 KVM Console Rackmount Keyboard DK Monitor HP TFT7600 G2 KVM Console Rackmount Keyboard NO Monitor **AZ877A** HP TFT7600 G2 KVM Console Rackmount Keyboard SE/FI Monitor **AZ878A** HP TFT7600 G2 KVM Console Rackmount Keyboard CH Monitor AZ879A HP TFT7600 G2 KVM Console Rackmount Keyboard PT Monitor AZ880A HP TFT7600 G2 KVM Console Rackmount Keyboard BE Monitor AZ881A HP TFT7600 G2 KVM Console Rackmount Keyboard JP Monitor AZ882A HP TFT7600 G2 KVM Console Rackmount Keyboard RU Monitor AZ883A HP TFT7600 G2 KVM Console Rackmount Keyboard Intl Monitor AZ884A AZ885A HP TFT7600 G2 KVM Console Rackmount Keyboard US TAA Monitor NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/13731 div/13731 div.html (Worldwide) **HP Server Console Switches** HP Server Console 0x2x8 Port Analog Switch **AF616A** HP Server Console 0x2x16 Port Analog Switch AF617A HP TAA 0x2x16xKVM Server Console G2 Switch AF626A NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/11834_div/11834_div.html (Worldwide) **HP Server Console Switch G2 with Virtual Media & CAC** HP 0x2x16 KVM Server Console Switch G2 with Virtual Media CAC Software **AF618A** HP 0x2x32 KVM Server Console Switch G2 with Virtual Media CAC Software **AF619A** HP KVM CAT5 1-pack USB Interface Adapter 336047-B21 NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/13475_div/13475_div.html (Worldwide) **HP IP Console Switch G2 with Virtual Media & CAC**



HP 1x1Ex8 KVM IP Console Switch G2 with Virtual Media CAC Software

HP 2x1Ex16 KVM IP Console Switch G2 with Virtual Media CAC Software

HP 1x4 USB/PS2 KVM Console Switch

AF611A

AF620A

AF621A

Additional Options

HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software

AF622A

NOTE: Please see the QuickSpecs for Technical Specifications and additional information:

http://h18000.www1.hp.com/products/quickspecs/13474_div/13474_div.html (Worldwide)

Rack Kits

HP Tower to Rack Conversion Tray Kit

659488-B21

HP USB and SD Options HP Flash Media Kits for USB Drives

NOTE: HP qualified blank USB key for use with HP ProLiant servers that support the VMware virtualization environment and other HP value-add software. HP recommends this industry standard USB flash device for use with VMware ESXi. USB device must be installed in the internal slot of the ProLiant server for use with VMware ESXi. Refer to HP VMware Getting Started Guide for installation instructions

HP 8GB USB Enterprise Mainstream Flash Media Drive Key Kit 737953-B21

HP Enterprise Performance Flash Media Kits for Memory Cards

HP 32GB SD Enterprise Mainstream Flash Media Kit 700136-B21

HP Enterprise Mainstream Flash Media Kits for Memory Cards

HP 8GB SD Enterprise Mainstream Flash Media Kit

726113-B21

NOTE: Blank SD media device is supported for use with VMware and Citrix. SD media must be installed in the internal slot of the ProLiant server. Learn more at: http://www.hp.com/go/proliantvirtualization.

NOTE: Please see the QuickSpecs for Technical Specifications and additional information:

http://h18000.www1.hp.com/products/quickspecs/13971 div/13971 div.html

HP Care Pack Services Proactive Care

NOTE: Collaborative Support plus Proactive services delivered by the onshore, local language Advanced Solution Center (ASC), end-to-end case ownership from a Technical Solution Specialists and Technical Account Manager who remotely delivers firmware/software revision management, proactive scans and incident trend reports. Recommended for customers running a virtualized infrastructure and/or customers who desire an enhanced call support experience.

HP 3 year 4 hour 24x7 ProLiant ML350(p) Proactive Care Service U3A78E HP 3 year 4 hour 24x7 with Defective Media Retention ProLiant ML350(p) U3A81E Proactive Care Service HP 3 year 6 hour Call To Repair 24x7 ProLiant ML350(p) Proactive Care Service U3A84E HP 3 year 6 hourCallToRepair 24x7 withDefective Media Retention ProLiant **U3A87E** ML350(p) Proactive Care SVC HP 3 year 4 hour 24x7 ProLiant ML350(p) with Insight Control Proactive Care **U3N77E** Service HP 3 year 4hr 24x7 with Defective Media Retention ML350(p) with Insight U3N80E Control Proactive Care SVC HP 3 year 6 hour Call To Repair 24x7 ProLiant ML350(p) with Insight Control **U3N83E** Proactive Care Service



Additional Options

HP 3yr 6hrCallToRepair 24x7w/Defective Media Retention ML350(p) w/Insight U3N86E Control Proactive Care SVC

Proactive Care Personalized Support Option

NOTE: To add an onsite Account Support Manager (ASM) to Proactive Care. ASM is an assigned resource who delivers support planning and brings technical expertise and best practices advices for the customer's environment.

HP 3 year ISS ProactiveCare Personalized Support

U6W98E

Installation Services

NOTE: Reduce the time required to get your system up and running and help minimize disruptions to your business.

HP Install ProLiant ML350(p) Service

HP Startup ProLiant ML350(p) Service

U4522E

U4523E

NOTE: For more information, customer/resellers can contact: http://www.hp.com/services/carepack



Memory

NOTE: Memory configurations listed do not apply to "Factory Integrated Models".

DDR3 memory population guidelines

For detailed memory configuration rules and guidelines, please use the Online DDR3 Memory Configuration Tool: www.hp.com/go/ddr3memory-configurator

General Guidelines:

- White DIMM slots denote the first slot of a channel. For 1 DPC (DIMM per channel) populate white slots only.
- Install DIMMs only if the corresponding processor is installed.
- If only one processor is installed in a two processor system, only half of the DIMM slots are available.
- To maximize performance, balance the total memory capacity between all installed processors
 - Populate DIMMs from heaviest load (quad-rank) to lightest load (single-rank) within a channel
 - O Heaviest load (DIMM with most ranks) within a channel goes furthest from the processor
- Do not mix UDIMMs, RDIMMs or LRDIMMs
- Quad rank LR DIMMs are supported at 3 DIMMs per channel.
- DIMMs of different voltages (1.35V & 1.5V) may be mixed in any order
 - O The system will power them at the higher voltage
- DIMMs of different speed grades may be mixed in any order
 - O The system will select a common optimal speed
- Memory speed is a function of the processor QPI bus speed.

Population Guidelines:

- There are four (4) channels per processor; eight (8) channels per server
- There are three (3) DIMM slots for each memory channel; twenty-four (24) total slots
- Memory channels1 and 3 consists of the three (3) DIMMs that are furthest from the processor
- Memory channel 2 and 4 consists of the three (3) DIMMs that are closest to the processor

ML350p Gen8-IVB Supported Memory Bandwidth and Capacity Treaty																
		I	Registe	red DI	MMS (R	DIMMs)		Load	Unbuffered with ECC DIMMs (UDIMMs)					MMs)	
DIMM									Reduced							
Туре									(LRDIMMs))						
DIMM	Single Rank (1R)			R)	1	Dual Ra	ank (2R)	Quad	Singl	e Rank	Dual Rank (2R)				
Rank									Rank (4R)	(1	IR)					
DIMM Capacity	4GB	4GB	8GB	8GB	8GB	8GB	16GB	16GB	32GB	2GB	2GB	4GB	4GB	8GB	8GB	
DIMM Native Speed (MHz)	1600	1866	1600	1866	1600	1866	1600	1866	1866	1600	1866	1600	1866	1600	1866	
Voltage	LV	Std	LV	Std	LV	Std	LV	Std	Std	LV	Std	LV	Std	LV	Std	
SLOTS T	HAT C	AN BE	POPUL	ATED												
24 slot servers	24	24	24	24	24	24	24	24	24	16	16	16	16	16	16	
MAXIMU	M CAP	ACITY (GB)*											N		
24 slot servers	96	96	192	192	192	192	384	384	768	32	32	64	64	128	128	
POPULA	TED DI	MM SP	EED (N	IHz)												



Memory

1 DIMM Per Channel	1600	1866	1600	1866	1600	1866	1600	1866	1866**	1600	1866	1600	1866	1600	1866
2 DIMM Per Channel	1600	1866	1600	1866	1600	1866	1600	1866	1866**	1600	1866****	1600	1866****	1600	1866****
3 DIMM Per Channel	800	1333	800	1333	800	1333	800	1333	1333***	n/a	n/a	n/a	n/a	n/a	n/a

NOTES:

Memory speed is a function of the processor QPI bus speed.

To realize the performance memory capabilities listed above HP SmartMemory is required.

- * Maximum capacity will vary based on individual server platform qualification schedule
- ** For HP SmartMemory RDIMM supports up to 3DPC@1066 at 1.35V. Third party memory may only support up to 3DPC@1066 at 1.5V.
- *** LRDIMM enables 3 DIMMs per channel. HP SmartMemory will supports up to 3DPC@DDR3-1066 at 1.35V. Third party memory may only support 3DPC @DDR3-1066 at 1.5V.
- **** For HP SmartMemory, UDIMM is, supported at 2DPC@1333. Third party memory may only support up to 2DPC@1066. ## RBSU setting required

ML350p	Gen8-IV	B Supp	orted M	emory E	Bandwid	th and	Capacity	У							
DIMM Type								Load Reduced (LRDIMMs)							
DIMM Rank	Sing	jle Rank	(1R)		Dual Ra	ank (2R)		Quad Rank (4R)	_	Single Rank (1R)			Dual Rank (2R)		
DIMM Capacity	4GB	4GB	8GB	8GB	8GB	16GB	16GB	32GB	2GB	2GB	4GB	4GB	8GB	8GB	
DIMM Native Speed (MHz)	1333	1600	1600	1333	1600	1333	1600	1333	1333	1600	1333	1600	1333	1600	
Voltage	LV	Std	Std	LV	Std	LV	Std	LV	LV	Std	LV	Std	LV	Std	
SLOTS T	HAT CA	N BE PO	DPULAT	ED				<u> </u>	<u> </u>						
24 slot servers	24	24	24	24	24	24	24	24	16	16	16	16	16	16	
MAXIMU	и сара	CITY (G	R*												
24 slot servers	96	96	192	192	192	384	384	768	32	32	64	64	128	128	
DODIII A		AM ODE		<u> </u>											
POPULA 1 DIMM Per Channel	1333	1600	1600	1333	1600	1333	1600	1333**	1333	1600	1333	1600	1333	1600	
2 DIMM Per Channel	1333	1600	1600	1333	1600	1333	1600	1333**	1333***	1600	1333***	1600	1333***	1600	



Memory

3 DIMM Per	800	1066	1066	800	1066	800	1066	1066	n/a	n/a	n/a	n/a	n/a	n/a
Channel														

NOTES:

Memory speed is a function of the processor QPI bus speed.

To realize the performance memory capabilities listed above HP SmartMemory is required.

- * Maximum capacity will vary based on individual server platform qualification schedule
- ** LRDIMM enables 3 DIMMs per channel. HP SmartMemory will supports up to 3DPC@DDR3-1066 at 1.35V. Third party memory may only support 3DPC @DDR3-1066 at 1.5V.
- *** For HP SmartMemory, UDIMM is, supported at 2DPC@1333. Third party memory may only support up to 2DPC@1066.

Memory Speed by Processor Model

<u>Processor Models</u>	Supported Memory Speeds
E5-2680, E5-2670, E5-2667, E5-2665, E5-2660, E5-2650, E5-2650L, E5-2637	7 1600/1333/1066MHz
E5-2640, E5-2630, E5-2630L, E5-2620	1333/1066MHz
E5-2609, E5-2603	1066MHz
E5-2697 v2, E5-2690 v2, E5-2670 v2, E5-2667 v2, E5-2650 v2, E5-2643 v2, E5 v2	5-2637 1866/1600/1333/1066MHz
E5-2640 v2, E5-2630 v2, E5-2630L v2, E5-2620 v2	1600/1333/1066MHz
E5-2609 v2, E5-2603 v2	1333/1066MHz

Standard and Maximum Memory Capacity (Pre-configured Models)

Pre Configured Models		Standard Memory	Maximum Memory Plus	Standard Memory Replaced with Optional
			Optional Memory	Memory
	Intel Xeon E5-2640	16GB (4x 4GB)	336GB (20x16GB, 4x4GB)	768GB (24 x 32GB)
	Intel Xeon E5-2620	8GB (2x 4GB)	360GB (22x16GB, 2x4GB)	768GB (24 x 32GB)
	Intel Xeon E5-2603	4GB (1x 4GB)	372GB (23x16GB, 1x4GB)	768GB (24 x 32GB)
	Intel Xeon E5-2640 v2	16GB (2x 8GB)	336GB (20x16GB, 4x4GB)	768GB (24 x 32GB)
	Intel Xeon E5-2620 v2	8GB (1x 8GB)	360GB (22x16GB, 2x4GB)	768GB (24 x 32GB)
	Intel Xeon E5-2609 v2	4GB (1x 4GB)	372GB (23x16GB, 1x4GB)	768GB (24 x 32GB)

DIMM slot and configuration diagrams

Basic memory slot & population diagram

• Population order; start with "A" first, "B" second, "C" third, etc.



Memory

		24 DIMM SLOTS	(12 per CPU node)		
	slot #	population order	slot#	population order	
Chnl 1	1	Α	1	Α	Chnl 1
	2	I	2	I	
	3	Е	3	Е	
Chnl 2	4	В	4	В	Chnl 2
	5	F	5	F	
	6	J	6	J	
	Proce	essor 1	Proce	essor 2	
Chnl 4	7	L	7	L	Chnl 4
	8	Н	8	Н	
	9	D	9	D	
Chnl 3	10	K	10	K	Chnl 3
	11	G	11	G	
	12	С	12	С	

Standard memory configuration (1 CPU model)

• 16GB, consisting of two (2) 8GB dual-rank PC3L-10600R-9 RDIMMs (Base Model)

	<u> </u>		·	<u> </u>	
	slot #	population order	slot#	population order	
Chnl 1	1	A; 8GB RDIMM	1	A; empty	Chnl 1
	2	E; empty	2	E; empty	
	3	I; empty	3	I; empty	ļ
Chnl 2	4	B; 8GB RDIMM	4	B; empty	Chnl 2
Offin 2	5	F; empty	5	F; empty	
	6	J; empty	6	J; empty	1
	Proce	ssor 1	Proce	ssor 2	
Chnl 4	7	I; empty	7	L; empty	Chnl 4
	8	H; empty	8	H; empty	
	9	D; empty	9	D; empty	
Chnl 3	10	K; empty	10	K; empty	Chnl 3
	11	G; empty	11	G; empty	_
	12	C; empty	12	C; empty	

Standard memory plus optional memory (1 CPU model)

- 48GB, consisting of two (2) 4GB RDIMMs plus ten (10) 4GB RDIMMs (Base Model)
 - o 12x 4GB dual-rank PC3L-10600R-9 RDIMMs



Memory

	slot #	population order	slot#	population order	
Chnl 1	1	A; 4GB RDIMM	1	A; empty	Chnl 1
	2	E; 4GB RDIMM	2	E; empty	
	3	I; 4GB RDIMM	3	I; empty	
		D 400 00 1144		<u> </u>	01.10
Chnl 2	4	B; 4GB RDIMM	4	B; empty	Chnl 2
	5	B; 4GB RDIMM	5	F; empty	
	6	J; 4GB RDIMM	6	J; empty	
	Proce	essor 1	Proce	ssor 2	
Chnl 4	7	L; 4GB RDIMM	7	L; empty	Chnl 4
	8	H; 4GB RDIMM	8	H; empty	
	9	D; 4GB RDIMM	9	D; empty	
Chnl 3	10	K; 4GB RDIMM	10	K; empty	Chnl 3
	11	G; 4GB RDIMM	11	G; empty	
	12	C; 4GB RDIMM	12	C; empty	

Standard memory replaced with optional memory (1 CPU model) RDIMM maximum configuration (1 CPU model)

• 192GB, consisting of twelve (12) 16GB dual-rank PC3L-10600R-9 RDIMMs

	slot #	population order	slot#	population order	
Chnl 1	1	A; 16GB RDIMM	1	A; empty	Chnl 1
	2	E; 16GB RDIMM	2	E; empty]
	3	I; 16GB RDIMM	3	I; empty]
Chnl 2	4	B; 16GB RDIMM	4	B; empty	Chnl 2
	5	F; 16GB RDIMM	5	F; empty	
	6	J; 16GB RDIMM	6	J; empty	
	Proce	essor 1	Proce	ssor 2	
Chnl 4	7	L; 16GB RDIMM	7	L; empty	Chnl 4
	8	H; 16GB RDIMM	8	H; empty	
	9	D; 16GB RDIMM	9	D; empty	
Chnl 3	10	K; 16GB RDIMM	10	K; empty	Chnl 3
	11	G; 16GB RDIMM	11	G; empty	
	12	C; 16GB RDIMM	12	C; empty	

UDIMM maximum configuration (1 CPU model)

• 64GB, consisting of eight (8) 8GB dual-rank PC3L-10600E-9 UDIMMs



Memory

	slot #	population order	slot#	population order	
Chnl 1	1	A; 8GB UDIMM	1	A; empty	Chnl 1
	2	E; 8GB UDIMM	2	E; empty	
	3	I; empty	3	I; empty	ļ
Chnl 2	4	B; 8GB UDIMM	4	B; empty	Chnl 2
	5	F; 8GB UDIMM	5	F; empty	
	6	J; empty	6	J; empty	
	Proce	essor 1	Proce	ssor 2	
Chnl 4	7	L; empty	7	L; empty	Chnl 4
	8	H; 8GB UDIMM	8	H; empty	
	9	D; 8GB UDIMM	9	D; empty	
Chnl 3	10	K; empty	10	K; empty	Chnl 3
	11	G; 8GB UDIMM	11	G; empty]
	12	C; 8GB UDIMM	12	C; empty	

Standard memory replaced with optional memory (2 CPU model) RDIMM maximum configuration (2 CPU model)

• 768GB, consisting of twenty four (24) 32GB quad-rank PC3L-10600LR-9 RDIMMs

	slot#	population order	slot#	population order	
Chnl 1	1	A; 32GB RDIMM	1	A; 32GB RDIMM	Chnl 1
	2	E; 32GB RDIMM	2	E; 32GB RDIMM	
	3	I; 32GB RDIMM	3	I; 32GB RDIMM	
Chnl 2	4	B; 32GB RDIMM	4	B; 32GB RDIMM	Chnl 2
	5	F; 32GB RDIMM	5	F; 32GB RDIMM	
	6	J; 32GB RDIMM	6	J; 32GB RDIMM	
	Proce	ssor 1	Proce	ssor 2	
Chnl 4	7	L; 32GB RDIMM	7	L; 32GB RDIMM	Chnl 4
	8	H; 32GB RDIMM	8	H; 32GB RDIMM	
	9	D; 32GB RDIMM	9	D; 32GB RDIMM	
Chnl 3	10	K;32GB DIMM	10	K;32GB DIMM	Chnl 3
	11	G;32GB DIMM	11	G;32GB DIMM	
	12	C;32GB DIMM	12	C;32GB DIMM	

UDIMM maximum configuration (2 CPU model)

• 128GB, consisting of sixteen (16) 8GB dual-rank PC3L-10600E-9 UDIMMs




Memory

	CI	CPU1		CPU2	
	slot #	population order	slot#	population order	
Chnl 1	1	A; 8GB UDIMM	1	A; 8GB UDIMM	Chnl 1
	2	E; 8GB UDIMM	2	E; 8GB UDIMM]
	3	I; empty	3	I; empty	
Chnl 2	4	B; 8GB UDIMM	4	B; 8GB UDIMM	Chnl 2
	5	F; 8GB UDIMM	5	F; 8GB UDIMM	1
	6	J; empty	6	J; empty]
	Proce	essor 1	Proce	essor 2	
Chnl 4	7	L; empty	7	L; empty	Chnl 4
	8	H; 8GB UDIMM	8	H; 8GB UDIMM]
	9	D; 8GB UDIMM	9	D; 8GB UDIMM	
Chnl 3	10	K; empty	10	K; empty	Chnl 3
	11	G; 8GB UDIMM	11	G; 8GB UDIMM	
	12	C; 8GB UDIMM	12	C; 8GB UDIMM]

NOTE: Capacity references are rounded to the common Gigabyte values.

- 1GB = 1024MB
- 2GB = 2048MB
- 4GB = 4096MB
- 8GB = 8192MB
- 16GB = 16384MB
- 32GB = 32768MB



Following are memory options available from HP:

HP Memory

NOTE: HP memory from previous generation servers are not qualified or warranted with this HP ProLiant Server. HP SmartMemory is required to realize the memory performance improvements and enhanced functionality listed in this document for Gen8. For additional information, please see the HP SmartMemory QuickSpecs at:

http://h18000.www1.hp.com/products/quickspecs/14225_div/14225_div.html **NOTE:** LRDIMM, RDIMM and UDIMMs are all distinct memory technologies and



Memory

cannot be mixed within a server. The majority of ProLiant Gen8 servers support RDIMM, UDIMM and LRDIMM. Registered DIMMs (RDIMMs) **NOTE:** The following memory is supported by the E5-2600 v2 series Processors. HP 4GB (1x4GB) Single Rank x4 PC3L-12800R (DDR3-1600) Registered CAS-713981-B21 11 Low Voltage Memory Kit HP 4GB (1x4GB) Single Rank x4 PC3-14900R (DDR3-1866) Registered CAS-13 708637-B21 Memory Kit HP 8GB (1x8GB) Dual Rank x4 PC3L-12800R (DDR3-1600) Registered CAS-11 713983-B21 Low Voltage Memory Kit HP 8GB (1x8GB) Single Rank x4 PC3L-12800R (DDR3-1600) Registered CAS-731765-B21 11 Low Voltage Memory Kit HP 8GB (1x8GB) Dual Rank x4 PC3-14900R (DDR3-1866) Registered CAS-13 708639-B21 Memory Kit HP 8GB (1x8GB) Single Rank x4 PC3-14900R (DDR3-1866) Registered CAS-13 731761-B21 Memory Kit HP 16GB (1x16GB) Dual Rank x4 PC3L-12800R (DDR3-1600) Registered CAS-713985-B21 11 Low Voltage Memory Kit HP 16GB (1x16GB) Dual Rank x4 PC3-14900R (DDR3-1866) Registered CAS-708641-B21 13 Memory Kit Registered DIMMs (RDIMMs) **NOTE:** The following memory is supported by the E5-2600 series Processors. HP 4GB (1x4GB) Single Rank x4 PC3L-10600R (DDR3-1333) Registered CAS-9 647893-B21 Low Voltage Memory Kit HP 4GB (1x4GB) Single Rank x4 PC3-12800R (DDR3-1600) Registered CAS-11 647895-B21 Memory Kit HP 8GB (1x8GB) Dual Rank x4 PC3L-10600R (DDR3-1333) Registered CAS-9 647897-B21 Low Voltage Memory Kit HP 8GB (1x8GB) Single Rank x4 PC3-12800R (DDR3-1600) Registered CAS-11 647899-B21 Memory Kit HP 8GB (1x8GB) Dual Rank x4 PC3-12800R (DDR3-1600) Registered CAS-11 690802-B21 Memory Kit HP 16GB (1x16GB) Dual Rank x4 PC3L-10600R (DDR3-1333) Registered CAS-647901-B21 9 Low Voltage Memory Kit HP 16GB (1x16GB) Dual Rank x4 PC3-12800R (DDR3-1600) Registered CAS-672631-B21 11 Memory Kit Unbuffered with ECC DIMMs (UDIMMs) **NOTE:** The following memory is supported by the E5-2600 v2 series Processors. HP 2GB (1x2GB) Single Rank x8 PC3L-12800E (DDR3-1600) Unbuffered CAS-713975-B21 11 Low Voltage Memory Kit HP 2GB (1x2GB) Single Rank x8 PC3-14900E (DDR3-1866) Unbuffered CAS-13 708631-B21 Memory Kit HP 4GB (1x4GB) Dual Rank x8 PC3L-12800E (DDR3-1600) Unbuffered CAS-11 713977-B21 Low Voltage Memory Kit HP 4GB (1x4GB) Dual Rank x8 PC3-14900E (DDR3-1866) Unbuffered CAS-13 708633-B21 Memory Kit HP 8GB (1x8GB) Dual Rank x8 PC3L-12800E (DDR3-1600) Unbuffered CAS-11 713979-B21 Low Voltage Memory Kit



Memory


HP 8GB (1x8GB) Dual Rank x8 PC3-14900E (DDR3-1866) Unbuffered CAS-13 Memory Kit	708635-B21
Unbuffered with ECC DIMMs (UDIMMs)	
NOTE: The following memory is supported by the E5-2600 series Processors.	
HP 2GB (1x2GB) Single Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory Kit	669320-B21
HP 2GB (1x2GB) Single Rank x8 PC3L-10600E (DDR3-1333) Unbuffered CAS-9 Low Voltage Memory Kit	647905-B21
HP 4GB (1x4GB) Dual Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory Kit	669322-B21
HP 4GB (1x4GB) Dual Rank x8 PC3L-10600E (DDR3-1333) Unbuffered CAS-9 Low Voltage Memory Kit	647907-B21
HP 8GB (1x8GB) Dual Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory Kit	669324-B21
HP 8GB (1x8GB) Dual Rank x8 PC3L-10600E (DDR3-1333) Unbuffered CAS-9 Low Voltage Memory Kit	647909-B21
Load Reduced DIMMs (LRDIMMs)	
NOTE: The following memory is supported by the E5-2600 v2 series Processors.	
HP 32GB (1x32GB) Quad Rank x4 PC3-14900L (DDR3-1866) Load Reduced CAS-13 Memory Kit	708643-B21
Load Reduced DIMMs (LRDIMMs)	
NOTE: The following memory is supported by the E5-2600 series Processors.	
HP 32GB (1x32GB) Quad Rank x4 PC3L-10600L (DDR3-1333) Load Reduced CAS-9 Low Voltage Memory Kit	647903-B21
NOTE: All DDR3 memory option kits consist of one DIMM per kit. For detailed memory configuration rules and guidelines, please use the Online DDR3 Memory Configuration Tool: www.hp.com/go/ddr3memory-configurator. NOTE: Depending on the memory configuration and processor model, 1600MHz and 1333MHz memory may operate at a lower speed. Please see the see the	

"Memory" section later in this document and the Online Memory Configuration Tool for details at www.hp.com/go/ddr3memory-configurator.



Storage





- 1 12
 12 x 3.5" (LFF) Hot-Plug SAS/SATA hard drive bays
 NOTE: Optional 2nd hard drive cage shown in configuration.
 - A Optical Drive
- B-C Available half height media bays, for up to two half height optical/tape drives or a single full height tape drive, or both can be populated with a third hard drive cage
- 1-16

 16 x 2.5" (SFF) Hot-Plug SAS/SATA hard drive bays

 NOTE: Optional 2nd hard drive cage shown in configuration
- A Optical Drive
- B-C Available half height media bays, for up to two half height optical/tape drives or a single, full height tape drives, or both can be populated with a third hard drive cage



Technical Specifications

System Unit Tower Dimensions 18.19 x 8.58 x 29.13 in (46.2 x 21.8 x 74.0 cm)

(H x W x D) (with feet/bezel)

Rack Dimensions 8.58 x 19.0 x 28.83 in. (21.8 x 48.26 x 73.22cm)

(H x W x D) (with feet/bezel)

Tower Weight Maximum 114.84 lb (52.09 kg)

(approximate) (all hard drives, power supplies, and processors

installed)

Minimum 70.33 lb (31.9 kg)

(one hard drive, power supply, and processor

installed)

Rack Weight Maximum 110.36 lb (50.06 kg)

(approximate) (all hard drives, power supplies, and processors

installed)

Minimum 60.91 lb (27.63 kg)

(one hard drive, power supply, and processor

installed)

Input Requirements Rated Line Voltage 100 to 240 VAC

(per power supply) Rated Input Current 7.1 Amps (at 120VAC) to 3.5 Amps (at 240

VAC)

Rated Input Frequency 50 to 60 Hz

Rated Input Power 852 W

BTU Rating Maximum 460W - 1773 BTU / hr (at 120 VAC), 1715 (at

240 VAC)

750W - 2892 BTU / hr (at 120 VAC), 2797 (at

240 VAC)

1200W - 3530 BTU / hr (at 120 VAC), 4600

(at 240 VAC)

Power Supply Output Rated Steady-State 460(750) W (at 100 VAC),

(per power supply) Power 460(750) W (at 200 VAC)

Maximum Peak Power 460(750) W (at 100 VAC),

460(750) W (at 200 VAC)

System Inlet Operating 10° to 35°C (50° to 95°F) at sea level with an **Temperature** altitude derating of 1.0°C per every 304.8 m

altitude derating of 1.0°C per every 304.8 m (1.8°F per every 1000 ft) above sea level to a maximum of 3048 m (10,000 ft), no direct sustained sunlight. Maximum rate of change is 10°C/hr (18°F/hr). The upper limit may be limited by the type and number of options

installed.

System performance may be reduced if operating with a fan fault or above 30°C

(86°F).



Technical Specifications

-30° to 60°C (-22° to 140°F). Maximum rate of Non-operating change is 20°C/hr (36°F/hr). **Relative Humidity** Operating 10 to 90% relative humidity (Rh), 28°C (non-condensing) (82.4°F) maximum wet bulb temperature, noncondensing. Non-operating 5 to 95% relative humidity (Rh), 38.7°C (101.7°F) maximum wet bulb temperature, non-condensing. **Altitude** 3048 m (10,000 ft). This value may be limited Operating by the type and number of options installed. Maximum allowable altitude change rate is 457 m/min (1500 ft/min). Non-operating 9144 m (30,000 ft). Maximum allowable altitude change rate is 457 m/min (1500 ft/min). **Acoustic Noise** Listed are the declared A-Weighted sound power levels (LWAd) and declared average bystander position A-Weighted sound pressure levels (LpAm) when the product is operating in a 23°C ambient environment. Noise emissions were measured in accordance with ISO 7779 (ECMA 74) and declared in accordance with ISO 9296 (ECMA 109). Idle L WAd 3.9 Bels (1P Non-Redundant) 4.2 Bels (2P Redundant) L pAm 22 dBA (1P Non-Redundant) 24 dBA (2P Redundant) Operating L WAd 4.0 Bels (1P Non-Redundant) 4.8 Bels (2P Redundant) L pAm 22 dBA (1P Non-Redundant) 30 dBA (2P Redundant) **NOTE:** The Listed sound levels apply to standard shipping configurations. Additional options may result in increased sound levels. **FCC Rating Emissions** Class B Classification (EMC) **Normative Standards** CISPR 22; EN55022; EN55024; FCC CFR 47, Pt 15; ICES-003; CNS13438; GB9254; K22;K24; EN 61000-3-2; EN 61000-3-3; EN 60950-1; IEC 60950-1

NOTE: Product conformance to cited product specifications is based on sample (type) testing, evaluation, or assessment. This product or family of products is eligible to bear the appropriate compliance logos and

statements.



Technical Specifications

HP Smart Array P420i Dimensions Controller

Embedded

Disk Drive and 6Gb/s SAS (Serial Attached SCSI) 3Gb/s SATA (Serial ATA)

Enclosure Interface -

Transfer rate

SAS Connectors 2 internal 4X connectors

Cache Memory Speed DDR3-1333MHz with 40 or 72-bit wide bus

Server Interface x8 PCIe 3.0 provides 32.0GB/s maximum bandwidth **SAS Speed** 8 6Gb/s SAS links provide 4.8GB/s maximum bandwidth

Cache Memory Zero Memory RAID has no cache memory

40-bit 512MB ECC protected Flash Backed Write Cache (FBWC)

72-bit 1GB and 2GB ECC protected FBWC

Logical Drives Supported **Host Memory**

Zero Memory, Up to 2 logical volumes (8 physical drives)

Up to 64 logical drives with cache

Addressing

64-bit, supporting greater than 4GB server memory space

RAID Support RAID 6, 60 (Advanced Data Guarding)

RAID 5, 50 (Distributed Data Guarding

NOTE: A minimum of 512 MB cache is required to enable RAID 5, 50, 6,

NOTE: HP Smart Array Advanced Pack (SAAP 2.0) is no longer required to enable RAID 6 & 60 (Advanced Data Guarding). However,

controller must be in firmware version 4.68 (or later).

RAID 1+0 (Striping & Mirroring) RAID 0 (Striping), RAID 1 (Mirroring)

HP Ethernet 1Gb 4-port Network Interface 331i Adapter Compatibility

10Base-T/100Base-TX/1000Base-TX

IEEE 802.3 10Base-T IEEE 802.3ab 1000Base-T

IEEE 802.3u 100Base-TX

Data Transfer Method

PCI Express, two lanes (x2)

Controller BCM5719

Network Transfer Rate 10Base-T (Half-Duplex) 10 Mb/s per port, 40 Mb/s Combined

> 10Base-T (Full-Duplex) 20 Mb/s per port, 80 Mb/s Combined 100Base-TX (Half-100 Mb/s per port, 400 Mb/s Combined

Duplex)

100Base-TX (Full-200 Mb/s per port, 800 Mb/s Combined

Duplex)

1000Base-TX (Half-1000Mb/s per port, 4000 Mb/s Combined

Duplex)

1000 Base-TX (Full-2000Mb/s per port, 8000 Mb/s Combined

Duplex)

Connector **RJ-45**

Cable Support 10Base-T Categories 3, 4 or 5 UTP; up to 328 ft (100 m)

> 10/100/1000Base-TX Category 5 or better; up to 328 ft (100 m)

Technical Specifications

Environment-friendly Products and Approach

End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return, trade-in, and recycling programs in many geographic areas. For trade-in information, please go to: http://www.hp.com/go/green. To recycle your product, please go to: http://www.hp.com/go/green or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/green. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

© Copyright 2014 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice.

Microsoft and Windows NT are US registered trademarks of Microsoft Corporation. Intel is a US registered trademark of Intel Corporation.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For hard drives, 1GB = 1 billion bytes. Actual formatted capacity is less.

