

FS-108E-POE Datasheet

Get a Quote

Overview

Fortinet FortiSwitch 108E-POE - switch - 8 ports - managed - rack-mountable.

Quick Specs

Figure 1 shows the appearance of FS-108E-POE.



Table 1 shows the Quick Specs.

| | |
|---------------------------|-------------------|
| Product Code | FS-108E-POE |
| Power Over Ethernet (PoE) | PoE+ |
| PoE Budget | 65 W |
| RAM | 256 MB DDR3 SDRAM |
| Flash Memory | 32 MB |

Product Details

Figure 2 shows the front panel of FS-108E-POE.



FS-108E-POE provides these features:

POE
managed
rack-mountable

Switch
4 x 10/100/1000 (PoE+) + 2 x Gigabit SFP + 4 x 10/100/1000

PoE+ (65 W)

Compare to Similar Items

Table 2 shows the comparison of FS-108E-POE.

| Module | FS-108E-POE | FS-124E |
|--------------|------------------------------------------------------------|------------------------------------|
| Ports | 4 x 10/100/1000 (PoE+) + 2 x Gigabit SFP + 4 x 10/100/1000 | 24 x 10/100/1000 + 4 x Gigabit SFP |
| Device Type | Switch - 8 ports - managed | Switch - 24 ports |
| RAM | 256 MB DDR3 SDRAM | 256 MB DDR3 SDRAM |
| Flash Memory | 32 MB | 32 MB |

Get More Information

Do you have any question about the **FS-108E-POE**?

Contact us now via [Live Chat](#) or sales@router-switch.com.

Specification

| FS-108E-POE Specification | |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General | |
| Device Type | Switch - 8 ports - managed |
| Enclosure Type | Rack-mountable 1U |
| Subtype | Gigabit Ethernet |
| Ports | 4 x 10/100/1000 (PoE+) + 2 x Gigabit SFP + 4 x 10/100/1000 |
| Power Over Ethernet (PoE) | PoE+ |
| PoE Budget | 65 W |
| Performance | Switching capacity: 20 Gbps Packet forwarding rate: 14.88 Mpps Latency: 4 μ s |
| Capacity | VLANs supported: 4000 Link aggregation groups: 8 Total link aggregation groups: 8 |
| MAC Address Table Size | 8K entries |
| Jumbo Frame Support | Yes |
| Remote Management Protocol | SNMP 1, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, SSH, CLI |
| Authentication Method | RADIUS |
| Features | Flow control, auto-negotiation, port mirroring, STP support, Spanning Tree Protocol (STP) support, Rapid Spanning Tree Protocol (RSTP) support, Multiple Spanning Tree Protocol (MSTP) support, Jumbo Frames support, STP Root Guard, fanless, Link Aggregation Control Protocol (LACP), DHCP client, Management Information Base (MIB), 512KB packet buffer, 802.1x authentication, Storm Control, Back Pressure Support, Link Aggregation, Management Information Base (MIB) II, Guest VLAN, STP BPDU Guard, IPv6 management, VLAN Tagging, FortiLink Mode, MAC Access Bypass (MAB), Telnet server |

| | |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Compliant Standards | IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3x, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ae, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3at, IEEE 802.1AX |
| RAM | 256 MB DDR3 SDRAM |
| Flash Memory | 32 MB |
| Status Indicators | Power, alarm, link/activity |
| Expansion / Connectivity | |
| Interfaces | 4 x 1000Base-T RJ-45 PoE+ 2 x Gigabit LAN SFP 1 x console RJ-45 management 4 x 1000Base-T RJ-45 |
| Power | |
| Power Device | Internal power supply |
| Voltage Required | AC 120/230 V (50 - 60 Hz) |
| Power Consumption Operational | 5.19 Watt |
| Miscellaneous | |
| MTBF | >10 years |
| Compliant Standards | UL, VCCI, BSMI, CB, FCC, RoHS2, RCM |
| Dimensions | |
| Width | 13 in |
| Depth | 8.2 in |
| Height | 1.7 in |
| Manufacturer Warranty | |
| Service & Support | Limited warranty - lifetime |
| Environmental Parameters | |
| Min Operating Temperature | 32 °F |
| Max Operating Temperature | 104 °F |
| Humidity Range Operating | 10 - 90% (non-condensing) |
| Min Storage Temperature | -40 °F |
| Max Storage Temperature | 158 °F |

Want to Buy

[Order Now](#)
[Get a Quote](#)

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.





200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com