

Overview

HPE 6125XLG Ethernet Blade Switch

The HPE 6125XLG Ethernet Blade Switch from HPE Networking is built with the enterprise data center in mind. The HPE 6125XLG is based on HPE Comware v7 network operating system, which delivers enterprise grade resiliency. The 6125XLG is designed for data center convergence with full support for IEEE Data Center Bridging (DCB) for lossless Ethernet, and Fibre Channel over Ethernet (FCoE) protocols. The Fibre Channel Forwarder (FCF) feature allows 3PAR StoreServ arrays to be directly attached to the HPE 6125XLG switch through FCoE ports. The HPE 6125XLG supports HPE Software-defined Network (SDN) ecosystem that delivers simple, open, and Enterprise ready benefits to automate the data center network. With support for IETF industry standard TRILL (Transparent Interconnection of Lots of Links) and SPB (Shortest Path Bridging), the HPE 6125XLG delivers loop free large Layer 2 networks with multi-path support. With the HPE Intelligent Resilient Fabric (IRF) multiple switches can be virtualized and managed as a single entity with the HPE Intelligent Management Center (IMC). The HPE 6125XLG is the industry's first blade switch with VEPA (Virtual Ethernet Port Aggregation) support, enabling customers to unify the management of their physical and virtual networks. Combine these features with Virtual Application Network (VAN) and your data center provides the benefits of versatility of a true Virtualized Network. HPE 6125XLG Ethernet Blade Switch provides flexibility, versatility, and resiliency making it the optimal choice for any blade switching environment.




Figure 1 HPE 6125XLG Blade Switch

- | | |
|----------------------------------|----------------------|
| 1. Ejector Lever | 6. Console port |
| 2. Four (4) 40 GbE (QSFP+) ports | 7. Port LED |
| 3. Release tab | 8. Health LED |
| 4. Eight (8) 10 GbE (SFP+) ports | 9. Unit ID (UID) LED |
| 5. Reset button | |

Models

HPE 6125XLG Ethernet Blade Switch
HPE 6125XLG Blade Switch

711307-B21
B9F40A

Compatibility

HPE ProLiant HPE ProLiant BL460c Gen9

Overview

Servers

HPE ProLiant BL660c Gen9
HPE ProLiant BL420c Gen8
HPE ProLiant BL460c Gen8
HPE ProLiant BL465c Gen8
HPE ProLiant BL660c Gen8
HPE ProLiant BL460 G7
HPE ProLiant BL465 G7
HPE ProLiant BL490 G7
HPE ProLiant BL620 G7
HPE ProLiant BL680 G7
HPE ProLiant BL685 G7

NOTE: Some servers listed above may be discontinued.

HPE Integrity Servers

HPE Integrity BL860c i2 Server Blade
HPE Integrity BL860c i4 Server Blade
HPE Integrity BL870c i2 Server Blade
HPE Integrity BL870c i4 Server Blade
HPE Integrity BL890c i2 Server Blade
HPE Integrity BL890c i4 Server Blade
HPE Integrity Superdome 2

NOTE: Some servers listed above may be discontinued.

ProLiant BL c-Class Server Blade Enclosures

HPE BladeSystem c7000 Enclosure

Standard Features

Standard Features

Performance

- 240Gb uplink bandwidth / 160Gb available server side bandwidth
- Dedicated 4x10Gb internal cross link ports between adjacent switches
- Non-blocking architecture
- Wire-speed switching and IPv4/IPv6 routing on all ports
- Supports FCoE N_Port Virtualization (NPV) and Fibre Channel Forwarder (FCF) modes
- Supports FCoE FIP Snooping mode
- Supports RoCE
- Combine up to 8 switches into a single virtual switch
- FCF provides a direct attach capability which allows attachment of 3PAR storage array FCoE ports directly to the switch
- QSFP+ ports support 4 x 10Gb with optional breakout cable
- SFP+ ports support either 1Gb or 10Gb depending on module inserted
- Any port can be used for IRF connections
- Cut-through switching
- Hardware-based wire-speed access control lists (ACLs)
- Data Center Bridging (DCBX)
- Support for VEPA (IEEE 802.1Qbg)

Management

- Remote configuration and management CLI
- Standards-based SNMP management via SNMPv1, v2c and v3
- Out of band management via Onboard Administrator
- HPE IMC Virtual Application Networking Fabric Manager
- Virtual Application Network (VAN)
- SDN with OpenFlow 1.3
- RJ45 console port
- sFlow
- Manager and operator privilege levels
- Command authorization via RADIUS
- Complete session logging for problem resolution
- LLDP Discovery protocol
- IPv6 management
- Multiple flash images
- Multiple configuration files
- Syslog
- Network Time Protocol (NTP)
- IEEE 1588v2 Precision Time Protocol (PTP)
- Software Defined Networks (SDN) / OpenFlow

Security

- IEEE 802.1X user authentication
- MAC-based authentication with RADIUS server
- Access Control Lists (ACLs)
- Secure FTP
- STP Root Guard
- DHCP Protection from unauthorized DHCP servers
- IP Source Guard
- Dynamic ARP protection to prevent eavesdropping

Standard Features

- Endpoint Admission Defense (EAD)
- RADIUS/TACACS+
- Secure management via SSHv2 and SNMPv3
- Unicast Reverse Path Forwarding (URPF)
- Monitor link and Smart link
- IPsec
- IKE (Internet Key Exchange)
- Disable password recovery

Layer 2 Switching

- 128K MAC addresses
- 4094 VLANs
- IEEE 802.1ad QinQ VLANs
- Per VLAN Spanning Tree (PVST+)
- Private VLANs (PVLAN)
- Multicast VLAN Registration Protocol (MVRP)
- Jumbo frame support
- Port Aggregation
- Spanning Tree Protocol, MSTP, RSTP, STP Root Guard
- IP Multicast Snooping and data-driven IGMP
- Transparent Interconnect of Lots of Links (TRILL)
- Shortest Path Bridging (SPB)
- Multiple Label Switching (MPLS)
- Virtual Private LAN Service (VPLS)

Layer 3 Routing

- IPv4 routing protocols - static routes, RIP, OSPF and BGP
- IPv6 routing protocols - static routes, RIPng, OSPFv3 and BGP+
- IPv6 tunneling
- IP Multicast - PIM-SSM, PIM-DM, PIM-SM, IGMP for IPv4 and IPv6
- Equal-Cost Multipath (ECMP)
- Policy-based routing
- DHCP and DHCPv6 client
- VRRP

Quality of Service (QoS)

- Advanced classifier-based QoS (with eight queues) - classifies traffic using multiple match criteria based on Layer 2, 3 and 4 information and applies QoS policies such as priority level and rate limit to selected traffic on a per-port or per-VLAN basis
- Traffic policing - supports Committed Access Rate (CAR) and line rate
- Powerful QoS feature - creates traffic classes based on access control lists (ACL), IEEE 802.1p precedence, IP, DSCP or Type of Service (ToS) precedence; supports filter, redirect, mirror or remark; supports the following congestion actions: strict priority (SP) queuing, weighted round robin (WRR), weighted fair queuing (WFQ), and weighted random early discard (WRED)
- Storm restraint - allows limitation of broadcast, multicast, and unknown unicast traffic rate to cut down on unwanted broadcast traffic on the network

Resiliency and

- Intelligent Resilient Fabric (IRF) - Creates virtual resilient switching fabrics, up to

Standard Features

High Availability

eight 6125XLG switches acting as a single Layer 2/3 switch; Switches do not have to be co-located and can be part of a disaster recovery system; Servers or switches can be attached using standard LACP for automatic load balancing and high availability; Simplifies network operation by eliminating Spanning Tree, ECMP and VRRP; IRF supports up to eight members in a group.

- Device Link Detection Protocol (DLDP) - Monitors Link connectivity and shuts down ports at both ends if unidirectional traffic is detected
- Virtual Router Redundancy Protocol (VRRP)

Monitoring and Diagnostics

- OAM (802.3ah) - Detects data link layer problems in the "last mile"; monitors link status between two devices
- CFD (802.1ag) - Connectivity Fault Detection (CFD) provides L2 link OAM mechanism used for link connectivity detection and fault location
- Mirroring - Port mirroring enables traffic on a port to be simultaneously sent to a network analyzer for monitoring; Flow-based mirroring

Service and Support

Service and Support

HPE Technology Services

When you buy HPE BladeSystem Options for your HPE BladeSystem, it is also good time to think about services. HPE Technology Services offers you technical consultants and support expertise to solve your most complex infrastructure problems, giving you one call to make, fast answers, and global reach. We help keep your business running, boost availability, and avoid downtime.

Protect your business beyond warranty with HPE Pointnext operational services

HPE Pointnext operational services provide total care and support expertise with committed response choices designed to meet your IT and business needs. HPE Foundation Care services offer scalable, reactive support-packages for Hewlett Packard Enterprise industry-standard servers and software. You can choose the type and level of service that is most suitable for your IT and business needs. HPE Collaborative Support offers hardware and basic software support with enhanced call management. If you are running business critical environments, Hewlett Packard Enterprise offers Proactive Care. This service helps you deliver high levels of system availability through proactive service management and advanced technical response.

Recommended HPE Pointnext operational services for your HPE product

Optimized Care HPE Proactive Care 3-Year 6-hour Call-to-Repair Response

Combined reactive and proactive support for hardware and software helping optimize your systems and delivering high levels of availability through proactive service management and advanced technical response. Hardware problem resolution to return the hardware in operating condition within 6 hours of the initial service request. A Technical Account Manager, as your single point of contact, will own your call or issue end to end until resolved.

<https://h20195.www2.hpe.com/v2/getpdf.aspx/4AA3-8855ENW.pdf>

HPE Installation of ProLiant Add On Options Service

This easy-to-buy, easy-to-use HPE Care Pack service helps ensure that your new Hewlett Packard Enterprise hardware is installed smoothly, efficiently, and with minimal disruption of your IT and business operations

Standard Care HPE Proactive Care 3-Year 24x7 4-hour Response

This service gives you combined reactive and proactive support including rapid access to our Advanced Solution Center to manage and prevent problems and a Technical Support Specialist with a broad level of technical knowledge that will engage with additional technical expertise as needed from the Hewlett Packard Enterprise vast global resources.

<https://www.hpe.com/us/en/services/proactive-care-services.html>

HPE Installation of ProLiant Add On Options Service

This easy-to-buy, easy-to-use HPE Care Pack service helps ensure that your new Hewlett Packard Enterprise hardware is installed smoothly, efficiently, and with minimal disruption of your IT and business operations.

Service and Support

Related Services **HPE Installation and Startup Service for HPE BladeSystem c-Class Enhanced Network**

HPE Provides for the configuration and testing of BladeSystem Ethernet interconnect switches to facilitate proper implementation of network protocols and access to advanced features.

<https://h20195.www2.hpe.com/v2/getpdf.aspx/4AA0-5964ENW.pdf>

HPE Proactive Care Personalized Support - Environmental Option

The Personalized Support option provides an assigned Account Support Manager who can bring best practices from across the industry plus extra technical skills to your IT team. This option is only available as an add-on to HPE Proactive Care Support.

HPE Proactive Select Service

Provides a flexible way to purchase Hewlett Packard Enterprise best-in-class consultancy and technical services. You can buy Proactive Select Service Credits when you purchase your hardware and then use the credits over the next 12 months.

<https://h20195.www2.hpe.com/v2/getpdf.aspx/4AA3-8855ENW.pdf>

NOTE: Additional HPE Pointnext operational services can be found at:

<http://hpe.com/info/cpc>

Insight Online/Insight Remote Support

HPE Insight Remote Support provides 24 X 7 remote monitoring, proactive notifications, and problem resolution. This comes at no additional cost with your Hewlett Packard Enterprise solution. Learn more about **Insight Remote Support** and **Insight Online**.

NOTE: [Insight Remote Support](#) is a prerequisite for [HPE Proactive Care](#)

HPE Support Center

Personalized online support portal with access to information, tools and experts to support Hewlett Packard Enterprise business products. Submit support cases online, chat with Hewlett Packard Enterprise experts, access support resources or collaborate with peers. Learn more <https://www.hpe.com/us/en/support.html>.

The HPE Support Center Mobile App allows you to resolve issues yourself or quickly connect to an agent for live support. Now, you can get access to personalized IT support anywhere, anytime.

HPE Insight Remote Support and HPE Support Center are available at no additional cost with a Hewlett Packard Enterprise warranty, HPE Care Pack or Hewlett Packard Enterprise contractual support agreement.

NOTE: [HPE Support Center Mobile App](#) above is subject to local availability.

Parts and materials

Hewlett Packard Enterprise will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product

Service and Support

quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by Hewlett Packard Enterprise due to malfunction.

Service Coverage

The HPE 6125XLG includes 3-years hardware support with next business day onsite response during standard business hours. If you have requirements for longer durations of service, faster response times or more comprehensive support, HPE Pointnext operational services for the HPE 6125XLG are available to uplift or extend your coverage.

For more information

To learn more about HPE BladeSystem services, please contact your Hewlett Packard Enterprise sales representative or Hewlett Packard Enterprise Authorized ServiceONE Channel Partner. Or visit: <http://www.hpe.com/services/bladestystem>

Related Options

SFP Options	HPE X120 1G SFP LC SX Transceiver	JD118B
	HPE X120 1G SFP LC LX Transceiver	JD119B
	HPE X125 1G SFP LC LH40 1310nm Transceiver	JD061A
	HPE X120 1G SFP LC LH40 1550nm Transceiver	JD062A
	HPE X125 1G SFP LC LH70 Transceiver	JD063B
	HPE X120 1G SFP RJ45 T Transceiver	JD089B

SFP+ Options	HPE X130 10G SFP+ LC SR Transceiver	JD092B
	HPE X130 10G SFP+ LC LRM Transceiver	JD093B
	HPE X130 10G SFP+ LC LR Transceiver	JD094B
	HPE X130 10G SFP+ LC ER 40km Transceiver	JG234A

QSFP+ Options	HPE X140 40G QSFP+ MPO SR4 Transceiver	JG325B
	HPE X140 40G QSFP+ LC BiDi 100m MM Transceiver	JL251A

Direct Attach Cables	HPE FlexNetwork X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable	JD095C
	HPE FlexNetwork X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable	JD096C
	HPE FlexNetwork X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	JD097C
	HPE FlexNetwork X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable	JG081C
	HPE FlexNetwork X240 10G SFP+ SFP+ 7m Direct Attach Copper Cable	JC784C
	HPE FlexNetwork X240 40G QSFP+ QSFP+ 1m Direct Attach Copper Cable	JG326A
	HPE FlexNetwork X240 40G QSFP+ QSFP+ 3m Direct Attach Copper Cable	JG327A
	HPE FlexNetwork X240 40G QSFP+ QSFP+ 5m Direct Attach Copper Cable	JG328A
	HPE FlexNetwork X240 40G QSFP+ to 4x10G SFP+ 1m Direct Attach Copper Splitter Cable	JG329A
	HPE FlexNetwork X240 40G QSFP+ to 4x10G SFP+ 3m Direct Attach Copper Splitter Cable	JG330A
	HPE FlexNetwork X240 40G QSFP+ to 4x10G SFP+ 5m Direct Attach Copper Splitter Cable	JG331A

Service and Support Offerings	Hardware Services On-site Service	
	HPE 3 year Proactive Care 24x7 6125XLG Service	U8K29E
	HPE 3 year Proactive Care Call to Repair 6125XLG Service	U8K35E

Related Options

Installation Services

HPE Installation of ProLiant Add On/In Options Service

UH745E

HPE BladSys c7000 Encd Network Startup Service

UE603E

NOTE: Additional HPE Pointnext operational services can be found at:

<http://hpe.com/info/cpc>

Technical Specifications

Shipping Dimensions	Length	11.54 in (293 mm)
	Width	14.57 in (370 mm)
	Height	3.54 in (95 mm)

Shipping Weight 2.1 kg (4.62 lbs)

Product Specifications Hardware	Performance	880Gbps throughput (8x10Gb and 4x40Gb uplink ports) 16x10Gb downlink (server) port 4 x10Gbps cross-link ports	
	Forwarding rate	14.8 million pps per 10 Gig port 59.2 million pps per 40 Gig port	
		Non-blocking, full-wire speed for all connections Auto-MDI/MDIX, auto-negotiation and auto-sensing with full-duplex support.	
	Forwarding Mode	Store and forward/Cut Through	
	Latency	1us (store and forward mode)	
	MAC Addresses	Supports 128K MAC addresses per switch in a BladeSystem Enclosure	
	Forwarding Table Age Time (Maximum age)	10 to 1,000,000 seconds (default: 300 seconds)	
	VLAN IDs	4094	
	Jumbo Frame	10K Bytes	
	IGMP Groups	1024	
	Memory	2 GB Main, 512MB flash and 9MB packet buffer	
	Connectors and Cabling	Connector	4 QSFP+ (40Gb/4 x10Gb/IRF) 8 SFP+/SFP (1Gb/10Gb/IRF) 1 RJ45 Management
		Cable Support	FCC Class A ICES-003 Class A AS/NZS 3548 Class A VCCI Class A
	Indicators	Module health, amber/green Module locator (UID), blue QSFP+ port link/activity, green SFP+ port link/activity, green	
Dimensions	Length	10.54 in (267.7 mm)	
	Width	7.59 in (192.8 mm)	
	Height	1.1 in (27.9 mm)	

Technical Specifications

Weight	2.0 kg (4.41 lbs)
Environmental Ranges	Temperature Range
	Operating 50° to 95° F (10° to 35° C)
	Non-operating -40° to 158° F (-40° to 70° C)
	Relative Humidity (non-condensing) Operating 10% to 90%
Power Specification	Power Requirements 95W

Standards Support

General protocols

IEEE 802.1ag Service Layer OAM
IEEE 802.1D MAC Bridges
IEEE 802.1p Priority
IEEE 802.1Q VLANs
IEEE 802.1Qbg Virtual Edge Bridging
IEEE 802.1s (MSTP)
IEEE 802.1v VLAN classification by Protocol and Port
IEEE 802.1w Rapid Reconfiguration of Spanning Tree
IEEE 802.1X PAE
IEEE 802.1AX / 802.3ad Link Aggregation Control Protocol (LACP)
IEEE 802.3ae 10 Gigabit Ethernet
IEEE 1588 v2 Precision Time Protocol (PTP)
RFC 768 UDP
RFC 792 ICMP
RFC 793 TCP
RFC 826 ARP
RFC 854 TELNET
RFC 925 Multi-LAN Address Resolution
RFC 951 BOOTP
RFC 1058 RIPv1
RFC 1350 TFTP Protocol (revision 2)
RFC 1519 CIDR
RFC 1542 BOOTP Extensions
RFC 2131 DHCP
RFC 2453 RIPv2
RFC 3768 VRRP
RFC 4675 RADIUS VLAN & Priority
802.1r GARP Proprietary Attribute Registration Protocol (GPRP)

FCoE

802.1Qaz DCBx
802.1Qaz ETS
802.1Qbb PFC
FIP Snooping
Fibre Channel Forwarder (FCF)
NPV mode

IP Multicast

RFC 2934 Protocol Independent Multicast MIB for IPv4

Technical Specifications

RFC 3376 IGMPv3 (host joins only)
RFC 3618 Multicast Source Discovery Protocol (MSDP)
RFC 3973 Draft 2 PIM Dense Mode
RFC 4601 PIM Sparse Mode

IPv6

RFC 4443 ICMPv6
RFC 4541 IGMP & MLD Snooping Switch
RFC 4861 IPv6 Neighbor Discovery
RFC 4862 IPv6 Stateless Address Auto-configuration

Layer 3

Static routes
RIP / RIPng
OSPF / OSPFv3
BGP / BGP+
IPv6 tunneling
PIM-SM
PIM-SSM
PIM-DM
IGMP
ECMP
Policy-based routing
DHCP and DHCPv6 client

MIBs

IEEE 8021ag CFM-MIB
IEEE 8021Q CFM-MIBv2
IEEE 8021AB LLDP-MIB
IEEE 8021AB LLDP-EXT-DOT1-MIB
IEEE 8021AB LLDP-EXT-DOT3-MIB
ANSI/TAA 1057 LLDP-EXT-MED-MIB
IEEE 8023 LAG-MIB
RFC 1213 MIB
RFC 1493 BRIDGE-MIB
RFC 2096 IP-FORWARD-MIB
RFC 2233 IF-MIB
RFC 2273 SNMP-NOTIFICATION-MIB
RFC 2571 SNMP-FRAMEWORK-MIB
RFC 2572 SNMP-MPD-MIB
RFC 2573 SNMP-TARGET-MIB
RFC 2674 P-BRIDGE-MIB
RFC 2674 Q-BRIDGE-MIB
RFC 3414 SNMP-USER-BASED-SM-MIB
RFC 3415 SNMP-VIEW-BASED-ACM-MIB
RFC 3417 SNMPv2-TM-MIB
RFC 3418 SNMPv2-MIB
RFC 3826 SNMP-USM-AES-MIB
RFC 4022 TCP-MIB
RFC 4044 FC-MGMT-MIB
RFC 4113 UDP-MIB
RFC 4133 ENTITY-MIB
RFC 4273 BGP4-MIB

Technical Specifications

RFC 4747 T11-FC-VIRTUAL-FABRIC-MIB
RFC 4750 OSPF-MIB
RFC 4750 OSPF-TRAP-MIB
RFC 4936 T11-FC-ZONE-SERVER-MIB
SFLOW-MIB (V5)

Safety and Compliance	Complies with UL 60950-1, CAN/CSA C22.2 No. 60950-1 and EN 60950-1. UL certified.
Safety	CE Marking
Certifications	RoHS 6/6 compliant

Electromagnetic Emissions	FCC Part 15 Class A
Certifications	EN 55022: 1998 (CISPR22)
FCC Part 15 Class A	EN 55024: 1998 (CISPR24)
	VCCI Class A
	AS/NZS 3548 Class A CE
	CNS 13438 Class A MIC
	MIC

Environment-friendly Products and Approach	End-of-life Management and Recycling	Hewlett Packard Enterprise offers end-of-life Hewlett Packard Enterprise product return, trade-in, and recycling programs in many geographic areas. For trade-in information, please go to http://www.hpe.com/info/recycle . To recycle your product, please go to http://www.hpe.com/info/recycle or contact your nearest Hewlett Packard Enterprise sales office. Products returned to Hewlett Packard Enterprise will be recycled, recovered or disposed of in a responsible manner.
---	---	---

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard Enterprise web site at: <http://www.hpe.com/info/recycle>. These instructions may be used by recyclers and other WEEE treatment facilities as well as Hewlett Packard Enterprise OEM customers who integrate and re-sell Hewlett Packard Enterprise equipment.

Summary of Changes

Date	Version History	Action	Description of Change
07-May-2018	Version 13	Changed	Overview and Service and Support sections were updated.
		Removed	OBS SKU was deleted: 737230-B21.
23-Oct-2017	Version 12	Changed	Care Pack naming and Service and Support-Parts and Materials updated.
05-Aug-2016	Version 11	Changed	Overview, Standard Features, Service and Support, and Related Options sections were updated.
		Added	SKU added in Related Options sections: JL251A
08-April-2016	Version 10	Changed	Minor changes made on Standard Features, SKU descriptions updated.
17-Dec-2015	Version 9	Changed	Changes made in High Availability and QSFP+ options sections.
01-Dec-2014	Version 8	Changed	Overview and Related Options section were updated
15-Aug-2014	Version 7	Changed	Product descriptions were revised in Related Options.
09-May-2014	Version 6	Changed	Changes made in the Standard Features and Related Options section.
17-Jan-2014	Version 5	Changed	Changes made in the Standard Features and Related Options section.
09-Dec-2013	Version 4	Changed	Correction made in the Overview introduction information.
30-Sep-2013	Version 3	Added	Added HPE 6125XLG Ethernet Blade Switch with TAA to the Models section.
13-Sep-2013	Version 2	Changed	Changes made to the Overview Section - Compatibility
10-Sep-2013	Version 1	Created	New QuickSpecs.



[Sign up for updates](#)

© Copyright 2018 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.



Microsoft and Windows are US registered trademarks of Microsoft Corporation.

c04111374 - 14612 - Worldwide - V13 - 7-May-2018